ESPECIFICACIONES TÉCNICAS

Pioneer™ Cordaje de posicionamiento de trabajo ajustable 2m

Pioneer™ Cordaje de posicionamiento de trabajo ajustable 2m / FAR0208



DESCRIPCIÓN

Longitud ajustable de hasta 2 m, hecha de correas de poliéster de 33 mm de ancho con un ajustador manual tipo anillo hecho de acero de aleación forjado para facilitar el ajuste.

OPCIONES

Pioneer™ Cordaje de posicionamiento de trabajo ajustable 2m (FAR0208)

NORMAS DE SEGURIDAD

EN 358

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

ESPECIFICACIONES

Longitud
2m max.

Extremos de cuerda
X

Dispositivo de ajuste
Regulador manual de anilla de acero aleado forjado

Se entrega con
2 Conectores de aluminio de cuarto de vuelta de ojo cautivo. Apertura del gatillo: 22 mm. Conforme a EN362 clase T

Material
Correas de poliéster de 33 mm

Manga protectora de cuerda

Peso del producto
587g

DESCARGAR

Colección de imágenes (ZIP)
doc-far0208-far0208e.pdf (PDF)

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.