

## Cordino di Posizionamento e Trattenuta Regolabile Pioneer™ 2m

Cordino di Posizionamento e Trattenuta Regolabile Pioneer™ fino a 2m / FAR0208



### DESCRIZIONE

Lunghezza regolabile fino a 2 m, realizzata in fettuccia di poliestere larga 33 mm regolazione manuale con anello in lega d'acciaio.

### OPZIONI

**Cordino di Posizionamento e Trattenuta Regolabile Pioneer™ fino a 2m (FAR0208)**

### STANDARD DI SICUREZZA

EN 358

## SPECIFICHE

Lunghezza  
**2m Max.**

Estremità Corda  
**X**

Dispositivo di Regolazione  
**Regolazione ad anello manuale in lega d'acciaio**

Consegnato con  
**2 connettori in alluminio a un quarto di giro non rimovibili. Apertura 22mm. Conforme a EN362 Classe T**

Materiale  
**Fettuccia in poliestere da 33 mm**

Manicotto di Protezione



Peso del Prodotto  
**587g**

## DOWNLOAD

 [Immagini Scaricabili \(ZIP\)](#)

 [doc-far0208-far0208e.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 4 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

