

Pioneer™ 2m regulowana linka do pozycjonowania pracy

Pioneer™ 2m regulowana linka do pozycjonowania pracy / FAR0208



OPIS

Regulowana długość do 2m, wykonana z taśmy poliestrowej o szerokości 33mm z ręcznym regulatorem typu pierścieniowego wykonanym z kutej stali stopowej dla ułatwienia regulacji.

OPCJE

Pioneer™ 2m regulowana linka do pozycjonowania pracy (FAR0208)

NORMY BEZPIECZEŃSTWA

EN 358



SPECYFIKACJE

Długość
2m max.

Końce lin
X

Urządzenie regulacyjne
Ręczna regulacja pierścieniowa z kutej stali stopowej

Dostarczane z
2 karabinki aluminiowe Typu Captive Eye 1/4 obrotu
Rozwarcie karabinka 22mm. Zgodny z EN362 Klasa
T

Materiał
Taśma poliestrowa 33mm

Rękaw ochronny liny
Nie



Waga Produktu
587g

PLIKI DO POBRANIA

 [Zbiór zdjęć \(ZIP\)](#)

 [doc-far0208-far0208e.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 4 Apr 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

