TECHNICAL SPECIFICATION



K2™ 3-Point Harness

K2™ 3-Point Harness / FAR0402



DESCRIPTION

The premium $K2^{TM}$ harness range combines quality materials with innovative features for optimum ergonomic performance, comfort, and safety.

This harness has a work positioning belt, parking loops and quick release buckles, with air mesh material and lightweight aluminium connectors.

OPTIONS

K2™ 3-Point Harness (FAR0402)

SAFETY STANDARDS

EN 361 • EN 358















SPECIFICATIONS

Anchorage Points

2

Fall Indicator

No

Work Postioning Belt

Yes

Lanyard Parking

Yes

Sub-Pelvic Strap

Yes

Metal Parts

Light Alloy Steel



Product Weight

2210g

Adjustment

Shoulder, Chest and Legs

Quick Release Buckles

Yes

Tool Keeper

Yes

Comfort Padding

Yes

Product Label Protected



Rated Weight / Load

140kg

FEATURES



Quick Release Buckles

Quick release buckles for quick and effortless fitting.



Tool Keepers

K2™ 3-point and 5-point harnesses feature tool keepers for safely stowing tools.



Lanyard Keepers

Breakaway clips safely store unused lanyards and release in the event of a fall.



Breathable Material

Air mesh material gives harnesses breathability and anti-tangle feature.



Inspection Labels

Inspection labels and user information protected in PVC pouch.



Ultimate Comfort

Polyester padding in leg, back and waist areas for improved comfort.

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Geo Technical Steel Frame

Telecomms

RANGE



VIDEOS

youtu.be/_QUfxDLufkA

DOWNLOADS



Image Pack (ZIP)



doc-far0401-far0402-far0403.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





