

TECHNICAL SPECIFICATION



2m Self-Retractable Lifeline with Scaffold Hook

2m Self-Retractable Lifeline with Scaffold Hook / FAR0731



DESCRIPTION

2m lightweight self-retractable lifeline, in robust and durable plastic casing. Webbing width 21mm with shock absorber. Equipped with 1 quarter turn gate aluminium connector and 1 aluminium scaffold hook.

Horizontal use (Sharp Edge VG 11 RFU CNB/P/11.060), fall factor 2 use in the limit of 100kg.

OPTIONS

2m Self-Retractable Lifeline with Scaffold Hook (FAR0731)

SAFETY STANDARDS

EN 360



SPECIFICATIONS

Fall Indicator
No

Length
2m

Material
21mm Wide Webbing

Shock Absorber
External

Sharp Edge
Yes

Casing
Robust and Durable Plastic



Rated Weight / Load
140kg (100kg For Horizontal and Fall Factor 2 Use)



Product Weight
1244g

Delivered With
1 Quarter Turn Aluminium Connector. Gate
Opening 21mm. Conforms to EN362 Class B. 1
Aluminium Scaffold Hook. Gate Opening 60mm.
Conforms to EN362 Class A/T

DOWNLOADS

[Image Pack \(ZIP\)](#)

[doc-far0701-far0731.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jpsafety.com / Web: www.jpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 16 Feb 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

