FICHE TECHNIQUE

Chargeur voiture Li-Ion Powercap® Active™ (4.2V)

Chargeur voiture Li-Ion Powercap® Active™ (4.2V) / CAU270-000-000



DESCRIPTION

Chargeur voiture pour Powercap® Active™ (4.2V)

OPTIONS

Chargeur voiture Li-Ion Powercap® Active™ (4.2V) (CAU270-000-000)

CARACTÉRISTIQUES



Powered Air

Protection to EN 12941 TH1P provides a cooling, comfortable supply of filtered air at 160 litres per minute, eliminating breathing resistance and visor misting.



Micro USB Charging

PowerCap® Active™ is supplied with a micro USB cable for recharging in as little as 5 hours. The PowerBox™1 battery pack features a built-in fuel gauge, making it easy to check charge level.



Casquette anti-heurts

The cap uses JSP HardCap™ A1+ bump cap technology, exceeding the EN 812 standard. The cap cover is easily removable, wipeable and machine washable.

GAMME

VIDÉOS

youtu.be/0yFoliUPusM

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

TÉLÉCHARGEMENTS

Pack d'images (ZIP)

doc-powercap_active.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.