TECHNISCHE SPECIFICATIES

Powercap® Active™ Li-Ion-autolader (4,2V)

Powercap® Active™ Li-Ion-autolader (4,2V) / CAU270-000-000



BESCHRIJVING

Autolader voor Powercap® Active™ (4,2V)

OPTIES

Powercap® Active™ Li-Ion-autolader (4,2V) (CAU270-000-000)

KENMERKEN



Powered Air

Bescherming volgens EN 12941 TH1P zorgt voor een verkoelende, comfortabele toevoer van gefilterde lucht met een snelheid van 160 liter per minuut, waardoor ademweerstand en viziernevel worden geëlimineerd.



Micro USB opladen

PowerCap® Active™ wordt geleverd met een micro USB-kabel voor opladen in slechts 5 uur. De PowerBox™1-batterij heeft een ingebouwde niveaumeter, zodat je gemakkelijk het oplaadniveau kunt controleren.



Bump Cap Hoofdbescherming

De Cap maakt gebruik van JSP HardCap™ A1+ stootpet technologie, die de EN 812 norm overtreft. De kap is gemakkelijk afneembaar, afveegbaar en wasbaar in de wasmachine.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

BEREIK

POWERCAP Active

VIDEO'S

youtu.be/0yFoliUPusM

DOWNLOADS

Pakket afbeeldingen (ZIP)

doc-powercap_active.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.