

# EVOLite® Badge Mid Peak Wheel Vented

White / AJB173-400-100



#### DESCRIPTION

EVOLite® safety helmet with a clear plastic ID card holder that fits standard business card size identification. Simple push and slide mechanism. A lamp bracket can be positioned at the top of the unit.

#### OPTIONS

Blue (AJB173-400-500) Green (AJB173-400-300) Orange (AJB173-400-800) Red (AJB173-400-600) **White (AJB173-400-100)** Yellow (AJB173-400-200)

#### SAFETY STANDARDS

EN 397



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



SPECIFICATIONS			
	Peak Mid		Impact Resistance 50 Joules
+0+	Lateral Deformation Yes		Resistance to Molten Metals and Hot Solids (optional) $\ensuremath{\textbf{Yes}}$
☀	Maximum Temperature +50°C		Minimum Temperature -40°C
ABS	ABS Shell Yes	₹\$	Recyclable Shell
- - - - - - -  -	Textile Harness	3DÌ	Depth Adjustment 3D Harness
- ĈĦ	Wheel Ratchet Yes		Universal Accessories Slot Yes
	Ventilation Yes	°€€	Reflective Option Optional
	Integrated Eyewear Optional	<b>□</b> ≪≡	ID card holder Fitted
(bsi)	BSI Kitemark Yes	$\bigcirc$	Optional 2 point chinstrap (EN397 & EN 812 compliant) Optional
	Optional 4 point chinstrap (EN397 Compliant) Optional	$\overline{\checkmark}$	JSPCheck <b>Yes</b>
	Product Weight 341g	¢	Size 53-64cm

# FEATURES



## Supreme Comfort

A 6-point textile cradle harness system & Chamlon<sup>™</sup> cotton sweatband offer unrivalled comfort.



## Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. Available with either the Revolution® wheel ratchet or the OneTouch<sup>™</sup> slip ratchet.



#### Accessories

A universal attachment slot enables firm fitting of a range of Surefit<sup>™</sup> safety visors, and ear defenders. EVOSpec® Integrated eyewear is also available.



#### **ID Card Holder**

Clear plastic ID card holder that fits standard business card size identification. Simple push and slide mechanism. A lamp bracket can be positioned at the top of the unit.



#### **3D Adjustment**

The textile harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.





Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility / reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



#### JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



Page 2 of 3 / Issued 13 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

#### LOGO

- Back
- Sides





## DOWNLOADS

- Image Pack (ZIP)
- doc-invincible-evolite.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.