TECHNICAL SPECIFICATION



EVOLite® Skyworker™ Micro Peak Revolution®Wheel Ratchet Vented

Black / AJS260-001-100



DESCRIPTION

The EVOLite® Skyworker™ helmet has a suspension system and shell structure that has been designed to be used for industrial, mountaineering, rescue and leisure activities.

Helmets conforming to the EN 12492 mountaineering standard are impact tested with two 5kg strikers. A hemispherical striker is dropped from 2 metres onto the crown of the helmet and a flat striker from 500mm on to the front, rear or side by tilting the headform to 30°. In all cases, the transmitted force through the neck of the headform must not exceed 10kN. Two penetration tests with a 3kg pointed striker are also performed within a 50mm radius of the helmet's crown without making contact with the headform.

Meets the mandatory shock absorption and penetration resistance requirements of EN 397 industrial helmet standard.

OPTIONS

Black (AJS260-001-100)

Blue (AJS260-000-500)

Green (AJS260-000-300)

Grey (AJS260-000-400)

Orange (AJS260-000-800)

White (AJS260-000-100)

Yellow (AJS260-000-200)

SAFETY STANDARDS

EN 12492 • EN 397





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







SPECIFICATIONS



Peak Micro



Side Impact Resistance 25 Joules





Minimum Temperature -40°C



Recyclable Shell



Depth Adjustment 3D Harness



Universal Accessories Slot Yes



Re Or

Reflective Option Optional



BSI Kitemark

Yes



JSPCheck Yes



Size

53-64cm



Impact Resistance 100 Joules



Maximum Temperature

+50°C



ABS Shell



Textile Harness



Wheel Ratchet



Ve

Ventilation

Yes



ID card holder

Optional



Fitted 4 point chinstrap (EN12492 Compliant)

Fitted



Product Weight

382g

FEATURES



EPS Liner

Side, front and rear impact protection from the shock absorbing EPS liner. The liner is vented to increase comfort whilst maintaining a high protection factor.



CR2™ Reflective

Using Class RA2, high intensity reflective. CR2[™] is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



Most Secure Fit

Fully adjustable 4-point chinstrap with quick release buckle. Easy to use Revolution® wheel ratchet and 3D Adjustment that offers 1-2-3 point harness depth settings for a perfect fit.



Ventilation

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.



Supreme Comfort

6-point textile cradle harness system with 3D Adjustment offering 1-2-3 point harness depth settings and a Chamlon™ cotton sweatband.



Accessories

Universal attachment slots enable firm fitting of a range of safety visors and ear defenders.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







RANGE VIDEOS



www.youtube.com/watch?v=2X3TSz5STxw

DOWNLOADS



doc-evolite-skyworker.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





