

TECHNICAL SPECIFICATION



Swiss One LYSS

1LYSDG23CKN / 1LYSDG23CKN



DESCRIPTION

Discover the new Eyewear generation... Lyss™ eyewear with Swiss One Flexofit technology... Angle adjustable nose pad for exceptional fit and adjustment for any situation... Worker comfort for many facial profiles. Soft cushioning browguard, pantoscopic temples with 3 side inclination positions and a unique up and down inclinable nose bridge concept to fit all nose shapes. THE fully adjustable spectacle!

OPTIONS

1LYSBB23CKN (1LYSBB23CKN)
1LYSBY23CKN (1LYSBY23CKN)
1LYSDG23CKN (1LYSDG23CKN)
1LYSDG23SKN (1LYSDG23SKN)

SAFETY STANDARDS

EN 170 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 2 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
2C



Manufacture's Trademark Swiss One
Swiss One



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °
Maximum protection for glasses
F



Resistance to Surface Damage by Fine Particles (optional)
K

Excellence Coating (KN Anti-Scratch/Anti-Mist)
Yes

Soft Nose Pad
Yes

Soft End Tips - Flex Flat Temple Pressure Free
Yes



Product Weight
29g



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T



Resistance to fogging (optional)
N

Lens Base Curve
8

Up And Down Nose Adjustment
Yes

FLEXoFIT Technology
Yes

FEATURES



Anti-mist

Anti-mist



Lens Curve

Lens curve



Rotating Arms

Rotating arms



Adjustable Nose Pad

Adjustable nose pad



Anti-scratch

Anti-scratch



High Performance Coating

Anti-scratch / anti-fog high performance coating



Soft End Tips

Soft end tips



Flexofit Technology

Flexofit technology

RANGE



DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-lyss.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 2 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

