

EVO®2 Mid Peak OneTouch™ Slip Ratchet Vented

Orange / AJF030-000-800



DESCRIPTION

The EVO®2 Comfort Plus helmet combines a super strong shell for superior all day protection in the widest range of environments, with the comfort benefits of the new Evolution® 3D Adjustment[™] harness system. EVO®2 is a true evolution of the long-established MK®2 and MK®3 helmets. The EVO®2 retains the JSP signature styling while incorporating developments first seen in the EVO®8. Packed full of the latest protection technology and features.

OPTIONS

Black (AJF030-001-100) Blue (AJF030-000-500) Green (AJF030-000-300) Grey - AJF030-000-400 - Made To Order Min 240 units (AJF030-000-400)

Orange (AJF030-000-800)

Pink (AJF030-003-900) Red (AJF030-000-600) White (AJF030-000-100) Yellow (AJF030-000-200)

SAFETY STANDARDS

EN 397



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



SPECIFICATIONS



Peak Mid Resistance to Molten Metals and Hot Solids (optional) Yes Minimum Temperature -30°C Recyclable Shell



Depth Adjustment **3D Harness**



Yes **BSI Kitemark**

Universal Accessories Slot



ID card holder Optional

Yes

Product Weight 402g

FEATURES



Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. The OneTouch™ slip ratchet makes it simple to tighten to the perfect fit.



CR2 Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



Supreme Comfort

A traditional 6-point polyethylene harness making the EVO®2 the more economical choice, whilst still providing the same high performance as the EVO®3.



Ventilation Option

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.

LOGO

Front

Back



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.





3D Adjustment

Impact Resistance

Maximum Temperature

50 Joules

HDPE Shell

LDPE Harness

Slip Ratchet

Ventilation

Optional

JSPCheck

Reflective Option

+50°C

Yes

Yes

Slip

Yes

Yes

Size 53-64cm

····(@)`++

The polyethylene harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.

Accessories

Universal attachment slot enables firm fitting of a range of safety visors and ear defenders.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.

RANGE



VIDEOS

www.youtube.com/watch?v=n9qrN2U0LFk

DOWNLOADS

Image Pack (ZIP)

doc-invincible-evo2.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

