TECHNICAL SPECIFICATION

Stealth™ 9200 Faceshield Goggle N Rated

Stealth™ 9200 Faceshield Goggle N Rated / AGW010-603-000



DESCRIPTION

A unique combination of indirect vented goggle and face protection with a sleek modern design. The Stealth™ 9200 has been engineered to offer outstanding performance, comfort and looks.

OPTIONS

Stealth™ 9200 Faceshield Goggle N Rated (AGW010-603-000)

SAFETY STANDARDS

EN 166 • EN 170

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

RADIATION PROTECTION BREAKDOWN filtering effect Scale Number
2C

Manufacturer's Trademark
JSP Dagger

Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B

Protection from Liquid Droplets
3

Resistance to Molten Metals and Hot Solids (optional)
9

Product Weight
202g

LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2

Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1

The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5˚C and +55˚C) Optional
T

Protection from Large Dust Particles (up to 40 um grain size)
4

Resistance to fogging (optional)
N

FEATURES




Wraparound Lens

Large injection moulded spherical wraparound optically perfect lens for a clear field of vision. With anti-mist, anti-scratch and class 1 optics.



Adjustable

Wide elastic headband with easy quick release clipping buckle makes it comfortable and suitable for most head sizes.



Comfort

Ultra soft housing and dual injection frame provides a soft comfortable fit that moulds to fit almost any face shape.



Moveable Faceshield

Lighter than a standard faceshield, this polycarbonate model can be easily lifted out of the way when not in use.

RANGE

STEALTH 9200

DOWNLOADS

Image Pack (ZIP)
doc-stealth-9200.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.