# TECHNICAL SPECIFICATION



# EVOGuard®C4-MAX Industrial Visor

EVOGuard® C4-MAX Industrial Visor - EVO® VISTA® Compatible / ADA270-070-00C



# DESCRIPTION

EVOGuard®C high performance industrial visors provide comprehensive facial coverage without limiting movement. The optical class 1 visor range offers UV protection and a panoramic view with minimal distortion.

Fully compatible with EVOGuard® browguard systems and \*EVO® helmet models, the C4-MAX visor offers up to AT rated impact protection and features an integral chinguard for added coverage.

\*Excluding EVO®6100 range.

# OPTIONS

EVOGuard®C4-MAX (ADA270-070-000)

EVOGuard® C4-MAX Industrial Visor – EVO® VISTA® Compatible (ADA270-070-00C)

## SAFETY STANDARDS


EN 166 • EN 170















#### **SPECIFICATIONS**



RADIATION PROTECTION BREAKDOWN filtering effect Scale Number

2C



Manufacturer's Trademark

JSP Dagger



High Energy Impact resists a 6 mm, 0.86g ball @ 190 m/s Maximum protection for face shields

A - When Fitted to EVO® Helmet



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional

Τ



Resistance to Molten Metals and Hot Solids (optional)



Resistance to fogging (optional)

IV



BSI Kitemark Yes



**Product Weight** 

220g



Supplied With: EVO® 2,3,5,DS,Lite,Skyworker™
Arms. EVO8/EVOLite Badgeholder Arms.
EVOGuard® Browguard Mounting System

Lens Thickness - edge 1.70mm



LIGHT TRANSMISSION BREAKDOWN Lens Shade number



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)

1



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.

B - When Fitted To EVOGuard® Browguard



Protection from Liquid Splash

3



Resistance to Surface Damage by Fine Particles (optional)

K



Visor Length

21.5cm

Material

Polycarbonate Shield



Recyclable

Yes

Lens Thickness - centre 2.00mm

### **FEATURES**



#### Compatibility

EVOGuard® visors maximise compatibility with JSP half masks, disposable respirators, prescription glasses and the Sonis® helmet mounted ear defender range.



# **Impact**

Wide range of high performance visors offering up to A rated impact resistance when fitted to a safety helmet and medium energy impact protection with the EVOGuard® browguard.



#### **UV Protection**

Visor filters harmful UV radiation to protect the eyes whilst also offering high light transmission and enhanced colour recognition.



#### **Vision**

The optical class 1 visor offers a panoramic view with minimal distortion, ideal for comfortable all day wear.



# Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement. EVOGuard® MAX visors offer enhanced coverage with an integral chinguard.



#### **Helmet & Browguard Integration**

Compatible with EVO® helmet models and EVOGuard® browguard systems. Visor supplied with dual system clips for mounting to a helmet or browguard.





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







RANGE VIDEOS



www.youtube.com/watch?v=\_VnTgBRRT9E

# DOWNLOADS



doc-evoguard.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





