

TECHNICAL SPECIFICATION



F600 Series - VERTICAL FOLD FLAT DISPOSABLE DUST MASK

F600 SERIES F621 - Retail Box of 15 x 2 pack masks - FFP2 - VERTICAL FOLD FLAT DISPOSABLE DUST MASK / BGV120-000-T00



DESCRIPTION

Disposable vertical fold flat mask with mouldable nose bridge and foam pad on the inside for comfort and a firmer fit.

OPTIONS

F600 SERIES F621 - Retail Box of 15 x 2 pack masks - FFP2 - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGV120-000-T00)

F600 SERIES F622 - Retail Box of 10 x 2 pack masks - FFP2V - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGW170-000-T00)

F600 SERIES F631 - Box 40 - FFP3 - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGX130-000-Q00)

F600 SERIES F621 - Box of 40 - FFP2 - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGV120-000-Q00)

F600 SERIES F622 - Box of 30 - FFP2V - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGW170-000-S00)

F600 SERIES F632 - Box of 30 - FFP3V - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGR180-000-S00)

F600 SERIES F632 - Retail Box of 10 x 2 pack masks - FFP3V - VERTICAL FOLD FLAT DISPOSABLE DUST MASK (BGR180-000-T00)

SAFETY STANDARDS

EN 14683 • EN 149



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 13 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Classification
FFP2 (Filtering Facepiece Particulate)

Usage
NR (Non-Reusable)

Minimum Filtration Efficiency
94% For FFP2 Rated

Nominal Protection Factor
12

Mask Design
Vertical Fold Flat

Toggle Harness adjustment system
Yes

Latex free
Yes

Filter Shelf Life
5 Years

Individually Wrapped
Yes in packs of 2



Filter Type
P (Protects Against Solid and Liquid Aerosols)



Activated Carbon Layer
No

Maximum Total Inward Leakage (TIL)
8%

UK Assigned Protection Factor
10



Exhalation Valve
No



Nose Bridge
Moulded in mask

Mask Material
Polypropylene



Product Weight
6g (Approx)

FEATURES



Foam Padded Nose Bridge

A mouldable nose bridge and foam pad on the inside for comfort and a firmer fit.



Folds Flat

Fold flat design is compact and easy to carry in a pocket.



Toggle Adjustment

Toggle adjuster on each strap to achieve an effective facial fit.

RANGE

F600
SERIES

DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-f621.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 13 May 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

