

Swiss One LYSS

1LYSBY23CKN / 1LYSBY23CKN



DESCRIZIONE

Scopri la nuova generazione di occhiali... Occhiali Lyss™ con tecnologia Swiss One Flexofit... Nasello regolabile ad angolo per fit eccezionale e regolazione per qualsiasi situazione... Comfort del lavoratore per molti profili facciali. Dotato di protezione sopraccigliare antipolvere con morbido rivestimento, stanghette regolabili in 3 inclinazioni ed un esclusivo nasello inclinabile verso l'alto e verso il basso, Un occhiale completamente regolabile!

OPZIONI










1LYSBB23CKN (1LYSBB23CKN)
1LYSBY23CKN (1LYSBY23CKN)
1LYSDG23CKN (1LYSDG23CKN)
1LYSDG23SKN (1LYSDG23SKN)

STANDARD DI SICUREZZA

EN 170 • EN 166



SPECIFICHE

	RADIATION PROTECTION BREAKDOWN filtering effect Scale Number 2C		LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2
	Manufacture's Trademark Swiss One Swiss One		Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use) 1
	Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s ° Maximum protection for glasses F		The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional T
	Resistance to Surface Damage by Fine Particles (optional) K		Resistance to fogging (optional)
	Excellence Coating (KN Anti-Scratch/Anti-Mist) Si		Lens Base Curve 8
	Soft Nose Pad Si		Up And Down Nose Adjustment Si
	Soft End Tips - Flex Flat Temple Pressure Free Si		FLEXoFIT Technology Si
	Product Weight 29g		



CARATTERISTICHE

		Anti-appannamento Anti-appannamento			Anti-graffio Anti-graffio
		Curva della lente Curva della lente			Rivestimento ad alte prestazioni Rivestimento ad alte prestazioni antigraffio / antiappannamento
		Stanghette inclinabili Stanghette inclinabili			Estremità stanghette morbide Estremità stanghette morbide
		Nasello regolabile Nasello regolabile			Tecnologia Flexofit: Tecnologia Flexofit:

RANGE



DOWNLOAD

-  [Immagini Scaricabili \(ZIP\)](#)
-  [doc-lyss.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 21 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

