

## Zwitsers een LYSS

1LYSBY23CKN / 1LYSBY23CKN



### BESCHRIJVING

Ontdek de nieuwe brillengeneratie... Lyss™ brillen met Swiss One Flexofit-technologie... In hoek verstelbare neuskussentjes voor uitzonderlijke fit tuur en aanpassing voor elke situatie... Worker comfort voor vele gezichtsprofielen. Zacht dempende voorhoofdbeschermer, pantoscopische pootjes met 3 zijwaartse hellingsposities en een uniek op en neer kantelbaar neusbrugconcept voor alle neusvormen. HET volledig aanpasbare spektakel!

### OPTIES










1LYSBB23CKN (1LYSBB23CKN)  
**1LYSBY23CKN (1LYSBY23CKN)**  
1LYSDG23CKN (1LYSDG23CKN)  
1LYSDG23SKN (1LYSDG23SKN)

### VEILIGHEIDSNORMEN















EN 170 • EN 166



## SPECIFICATIES

	RADIATION PROTECTION BREAKDOWN filtering effect Scale Number 2C		LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1,2
	Manufacture's Trademark Swiss One Zwitsers		Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use) 1
	Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s ° Maximum protection for glasses F		The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional T
	Resistance to Surface Damage by Fine Particles (optional) K		Resistance to fogging (optional)
	Excellence Coating (KN Anti-Scratch/Anti-Mist) Ja		Lens Base Curve 8
	Soft Nose Pad Ja		Up And Down Nose Adjustment Ja
	Soft End Tips - Flex Flat Temple Pressure Free Ja		FLEXoFIT Technology Ja
	Product Weight 29g		

## KENMERKEN

		<b>Anti-mist</b> Anti-mist			<b>Antikras</b> Antikras
		<b>Lenskromme</b> Lenscurve			<b>Hoogwaardige coating</b> Krasbestendige / anticondenscoating met hoge prestaties
		<b>Roterende armen</b> Roterende armen			<b>Tips voor zachte uiteinden</b> Zachte uiteinden
		<b>Verstelbaar neuskussen</b> Verstelbaar neuskussentje			<b>Flexofit-technologie</b> Flexofit-technologie

## BEREIK



## DOWNLOADS

-  [Pakket afbeeldingen \(ZIP\)](#)
-  [doc-lyss.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 21 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

