

SPECYFIKACJA TECHNICZNA



Swiss One LYSS

1LYSBY23CKN / 1LYSBY23CKN



OPIS

Odkryj nową generację okularów... Okulary Lyss™ z technologią Swiss One Flexofit... Regulowany kąt nachylenia noska dla wyjątkowego dopasowania i regulacji w każdej sytuacji... Komfort pracy dla wielu kształtów twarzy. Miękki łuk brwiowy, pantoskopowe zauszniki z 3 pozycjami nachylenia bocznego oraz unikalny, odchylany w górę i w dół mostek nosowy, pasujący do wszystkich kształtów nosa. Okulary w pełni regulowane!

OPCJE

1LYSBB23CKN (1LYSBB23CKN)
1LYSBY23CKN (1LYSBY23CKN)
1LYSDG23CKN (1LYSDG23CKN)
1LYSDG23SKN (1LYSDG23SKN)

NORMY BEZPIECZEŃSTWA

EN 170 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.










Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 21 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECYFIKACJE

	RADIATION PROTECTION BREAKDOWN filtering effect Scale Number 2C		LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1,2
	Manufacture's Trademark Swiss One Swiss One		Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use) 1
	Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s ° Maximum protection for glasses F		The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional T
	Resistance to Surface Damage by Fine Particles (optional) K		Resistance to fogging (optional)
	Excellence Coating (KN Anti-Scratch/Anti-Mist) Tak		Lens Base Curve 8
	Soft Nose Pad Tak		Up And Down Nose Adjustment Tak
	Soft End Tips - Flex Flat Temple Pressure Free Tak		FLEXoFIT Technology Tak
	Product Weight 29g		


CECHY

		Nieparujące Nieparujące			Nierysujące Nierysujące
		Krzywizna soczewki Krzywizna soczewki			Powłoka o wysokiej wydajności Powłoka nierysująca / nieparująca o wysokiej wydajności
		Obrotowe ramiona Obrotowe ramiona			Miękkie końcówki Miękkie końcówki
		Regulowany nosek Regulowany nosek			Technologia Flexofit Technologia flexofit

GAMA



PLIKI DO POBRANIA

-  [Zbiór zdjęć \(ZIP\)](#)
-  [doc-lyss.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 21 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

