TECHNISCHE SPEZIFIKATION

EVO® ALTA™ DualSwitch™

Extra Visibility Yellow / ARD170-40C-700



BESCHREIBUNG

The new EVO®ALTA™ range offers all round impact protection. The mountaineering-style helmet features a specialised shell structure and internal liner to increase durability and shock absorption performance. Precise adjustment settings enable a secure fit, ensuring that the helmet remains stable.

Engineered to maximise compatibility and accessory integration, the EVO®ALTA™ range is an adaptive system with built-in attachment points, an interchangeable front module, and a selection of 4-point chinstraps for use in a wide range of applications.

EVO®ALTA™ DualSwitch™ features the unique JSP DualSwitch™ harness system. With the DualSwitch™ up and EN 397 indicated on the switch, EVO®ALTA™ is fully compliant to EN 397 and EN 50365:2002 with a 4-point chinstrap designed to release under force if caught or snagged. With the DualSwitch™ down and EN 12492 indicated on the switch, EVO®ALTA™ is fully compliant to EN 12492 and meets the electrical insulation performance requirements of EN 50365:2002 with a 4-point chinstrap designed to stay secure under force, maximising security during a fall.

OPTIONEN

Black (ARD170-401-100)
Blue (ARD170-400-500)
Extra Visibility Orange (ARD170-401-600)
Extra Visibility Yellow (ARD170-40C-700)
Green (ARD170-400-300)
Grey (ARD170-400-400)
Red (ARD170-400-600)
White (ARD170-400-100)

SICHERHEITSSTANDARDS

EN 12492 • EN 397 • EN 50365

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPEZIFIKATIONEN

Schirm
Mikro

Seitliche Schlagfestigkeit
25 Joules

Seitliche Verformung
Ja

Max. Temperatur
+50°C

ABS-Schale
Ja

Wiederverwendbar
Schale

Belüftung
Ja

Drehradverschluss
Ja

Universeller Zubehör-Steckplatz
Ja

ID-Ausweishalter
Optional

Produktgewicht
500g

Stoßfestigkeit
100 Joules

Schmelzmetall
Ja

EN 50365 ELEKTRISCHE ISOLIERUNG
1000V

Min. Temperatur
-40°C

EPP-Aufprall Absorber
Ja

Textil
Innenausstattung

Tiefeneinstellung
3D-Anpassung

Ausgestattet mit 4-Punkt-DualSwitch-Kinnriemen (entspricht: EN 4 und EN 397)
Ausgestattet

Reflektierendes CR2
Ja

JSPCheck
Ja

Größe
53-64cm

EIGENSCHAFTEN



All-Round Protection

EVO® ALTA™ provides all-round impact protection with top, side, front and rear shock absorption performance. The helmet is designed with an extended nape section to offer greater neck coverage.



Compatibility & Accessories

The EVO® Alta™ range maximises compatibility and accessory integration. Attachment points on the front, sides and rear of the helmet shell enable firm fitting of ear defenders, faceshields, goggle and lamp straps, plus a range of other accessories.



Maximum Comfort

The Revolution® Flex wheel ratchet harness secures the helmet, eliminating pressure points to provide maximum comfort. Fitted with a replaceable Chamlon™ cotton sweatband and fully compatible with EVO® cooling sweatbands for protection against heat stress.



Interchangeable Front Module

EVO® ALTA™ features a unique interchangeable front module. Select the integrated ID card holder for on-site identification or choose the logo-ready standard front to apply company branding. Both front modules enable attachment of a helmet lamp and other accessories.



EPP Liner

EVO® ALTA™ features an internal impact liner to increase shock absorption and penetration protection. Manufactured in expanded polypropylene (EPP), the liner is lightweight and ventilated for comfort.



Secure Fit

The harness cradles the head to keep the helmet stable with an adjustable 4-point chinstrap for increased security. 3D-Adjustment depth settings enable the most precise fit attainable on a safety helmet.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



4-Point Chinstrap

The 4-point chinstrap is easy to adjust on the head. Size and anchorage point adjustment enable a tailored fit for different head sizes, ensuring stability and greater comfort.



Dual Ventilation

Side and rear ventilation in the helmet's shell and liner reduce temperatures by an average 2-3 degrees.



Switch Up

Die Haltekraft für den Kinnriemen bei der EN 397 liegt zwischen 150 und 250 Newton. Damit das Risiko der Strangulation reduziert wird, wurde der Kinnriemen so konzipiert, dass er sich selbst bei einer Verhakung löst.



Custom Branding

Helmets can be customised to meet a corporate identity. Logo printing is available for the standard front module, helping to increase brand recognition and discourage theft. MOQs apply.



Switch Down

Die Haltekraft des Kinnriemens nach EN 12492 ist größer als 500 Newton. Dies vermindert das Risiko des Verlustes während eines Sturzes.

LOGO

- [x] Vorderseite
- [x] Beidseitig

SERIE

evolta™

DOWNLOADS

Bilderordner (ZIP)

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.