

## EVO® ALTA™ DualSwitch™

EVO® ALTA™ DualSwitch™ Vented Wheel Ratchet - High Visibility Yellow - CR2 / ARD170-40C-700



### BESCHREIBUNG

The new EVO® ALTA™ offers all-round impact protection. The mountaineering-style helmet features a specialised shell structure and internal liner to increase durability and shock absorption performance. Precise adjustment settings enable a secure fit, ensuring the helmet remains stable. Engineered to maximise compatibility and accessory integration, EVO® ALTA™ is an adaptive system with built-in attachment points and an interchangeable front module.

EVO® ALTA™ DualSwitch™ features the unique JSP DualSwitch™ harness system, certified to EN 12492 and EN 397 with a switch on the chinstrap. The 4-point chinstrap offers the ability to change between the two standards easily at the flick of a switch.

### OPTIONEN

EVO® ALTA™ DualSwitch™ Vented Wheel Ratchet - Black - CR2 (ARD170-401-100)

EVO® ALTA™ DualSwitch™ Vented Wheel Ratchet - Green - CR2 (ARD170-400-300)

EVO® ALTA™ DualSwitch™ Vented Wheel Ratchet - High Visibility Orange - CR2 (ARD170-401-600)

**EVO® ALTA™ DualSwitch™ Vented Wheel Ratchet - High Visibility Yellow - CR2 (ARD170-40C-700)**

EVO® ALTA™ DualSwitch™ Vented Wheel Ratchet - Red - CR2 (ARD170-400-600)

EVO® ALTA™ DualSwitch™ Vented Wheel Ratchet - White - CR2 (ARD170-400-100)

### SICHERHEITSSTANDARDS

EN 12492 • EN 397 • EN 50365



## SPEZIFIKATIONEN

Schirm  
Mikro

Seitliche Schlagfestigkeit  
25 Joules

Seitliche Verformung  
Ja

Max. Temperatur  
+50°C

ABS-Schale  
Ja

Wiederverwendbar  
Schale

Belüftung  
Ja

Drehradverschluss  
Ja

Universeller Zubehör-Steckplatz  
Ja

ID-KARTENHALTER  
Optional

Produktgewicht  
500g

Stoßfestigkeit  
100 Joules

Schmelzmetall  
Ja

EN 50365 ELEKTRISCHE ISOLIERUNG  
1000V

Min. Temperatur  
-40°C

EPP-Aufprall Absorber  
Ja

Textil  
Innenausstattung

Tiefeneinstellung  
3D-Anpassung

Ausgestattet mit 4-Punkt-DualSwitch-Kinnriemen (entspricht:  
EN 4 und EN 397)  
Ausgestattet

Reflektierendes CR2  
Optional

JSPCheck  
Ja

Größe  
53-64cm

## EIGENSCHAFTEN



### All-Round Protection

EVO® ALTA™ provides all-round impact protection with top, side, front and rear shock absorption performance. The helmet is designed with an extended nape section to offer greater neck coverage.




### Interchangeable Front Module

EVO® ALTA™ features a unique interchangeable front module. Select the integrated ID card holder for on-site identification or choose the logo-ready standard front to apply company branding. Both front modules enable attachment of a helmet lamp and other accessories.



### Compatibility & Accessories

The EVO® ALTA™ range maximises compatibility and accessory integration. Attachment points on the helmet shell enable firm fitting of ear defenders, faceshields, goggle and lamp straps, plus a range of other accessories.



### EPP Liner

EVO® ALTA™ features an internal impact liner to increase shock absorption and penetration protection. Manufactured in expanded polypropylene (EPP), the liner is lightweight and ventilated for comfort.



### Maximum Comfort

The Revolution® Flex wheel ratchet harness secures the helmet, eliminating pressure points to provide maximum comfort. Fitted with a replaceable Chamlon™ cotton sweatband and fully compatible with EVO® cooling sweatbands for protection against heat stress.



### Secure Fit

The harness cradles the head to keep the helmet stable with an adjustable 4-point chinstrap for increased security. 3D-Adjustment depth settings enable the most precise fit attainable on a safety helmet.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 7 Jul 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.





### 4-Point Chinstrap

The 4-point chinstrap is easy to adjust on the head. Size and anchorage point adjustment enable a tailored fit for different head sizes, ensuring stability and greater comfort.



### Dual Ventilation

Side and rear ventilation in the helmet's shell and liner reduce temperatures by an average 2-3 degrees.



### Switch Up

Die Haltekraft für den Kinnriemen bei der EN 397 liegt zwischen 150 und 250 Newton. Damit das Risiko der Strangulation reduziert wird, wurde der Kinnriemen so konzipiert, dass er sich selbst bei einer Verhakung löst.



### Custom Branding

Helmets can be customised to meet a corporate identity. Logo printing is available for the standard front module, helping to increase brand recognition and discourage theft. MOQs apply.



### Switch Down

Die Haltekraft des Kinnriemens nach EN 12492 ist größer als 500 Newton. Dies vermindert das Risiko des Verlustes während eines Sturzes.

#### LOGO

- Vorderseite
- Beidseitig

#### SERIE



#### DOWNLOADS

[Bilderordner \(ZIP\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsspsafety.com / Web: www.jsspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 7 Jul 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

