TECHNICAL SPECIFICATION



Typhoon™ Moulded Mask FFP3 Valved (735)

Box of 10 / BEK136-101-A00



DESCRIPTION

Moulded mask featuring our unique Typhoon $^{\text{TM}}$ Valve technology for extremely low exhale breathing resistance, and low CO2, heat and moisture build up.

• High efficiency (99% minimum) filtering

OPTIONS

Box of 10 (BEK136-101-A00)

SAFETY STANDARDS

EN 149















SPECIFICATIONS

Classification

FFP3 (Filtering Facepiece Particulate)

Usage

NR (Non-Reusable)



Activated Carbon Layer

No

Maximum Total Inward Leakage (TIL)

2%

UK Assigned Protection Factor

20



Exhalation Valve

Yes - JSP Typhoon Valve



Nose Bridge

Adjustable Aluminium

Metal Free

No

Filter Shelf Life

5 Years



Product Weight

29g



Filter Type

P (Protects Against Solid and Liquid Aerosols)



(D) Resistance to dust clogging

Yes - D marking = passes optional clogging test

Minimum Filtration Efficiency 99% For FFP3 Rated

Nominal Protection Factor

50

Mask Design Moulded

Buckle Type Harness adjustment system

Yes

Latex free

Yes

Mask Material Polypropylene



BSI Kitemark

Yes

FEATURES



Comfort

A 360° comfort foam area around the inside of the mask provides a perfect fit and maximum resistance.



Fit

The welded nose piece prevents any irritation, misshaping and gives a tighter fit. Adjustable strap means it can be fitted comfortably to all head sizes and shapes.



Typhoon™ Valve

The Unique Typhoon™ valve has been designed to reduce breathing resistance, heat and moisture build-up. The valve is unaffected by any moisture, and therefore can be used with the same performance under very low temperatures.

RANGE



DOWNLOADS

Image Pack (ZIP)

doc-olympus-700-series-735.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





