

# TECHNICAL SPECIFICATION



## Aerialine™ 20m Horizontal Lifeline

Aerialine™ 20m Horizontal Lifeline / FAR0804



### DESCRIPTION

Temporary flexible horizontal anchor line for spans of between 3m and 20m. Very easy to install (can be installed by one person). Tested for use for up to 2 persons.

### OPTIONS

**Aerialine™ 20m Horizontal Lifeline (FAR0804)**

### SAFETY STANDARDS

EN 795 • EN 362



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsspsafety.com / Web: www.jsspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 6 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Length  
20m

Material  
30mm Polyester Webbing.

Adjustment Device  
Ratchet Tensioning System



Product Weight  
3450g

Delivered With  
2 Anchorage Slings. Conforms to EN795 Type B. 2  
Twist Lock Connectors In Alloy Steel. Gate Opening  
22.5mm. Conforms to EN362 Class B.

## DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0804.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 6 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

