

TECHNICAL SPECIFICATION



Aerialine™ 20m Horizontal Lifeline

Aerialine™ 20m Horizontal Lifeline / FAR0804



DESCRIPTION

Temporary flexible horizontal anchor line for spans of between 3m and 20m. Very easy to install (can be installed by one person). Tested for use for up to 2 persons.

OPTIONS

Aerialine™ 20m Horizontal Lifeline (FAR0804)

SAFETY STANDARDS

EN 795 • EN 362



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jpsafety.com / Web: www.jpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 25 Jan 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Length
20m

Material
30mm Polyester Webbing.

Adjustment Device
Ratchet Tensioning System



Product Weight
3450g

Delivered With
2 Anchorage Slings. Conforms to EN795 Type B. 2
Twist Lock Connectors In Alloy Steel. Gate Opening
22.5mm. Conforms to EN362 Class B.

DOWNLOADS

-  [Image Pack \(ZIP\)](#)
-  [doc-far0804.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jpsafety.com / Web: www.jpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 25 Jan 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

