

TECHNICAL SPECIFICATION



EVO® Goggle Single Lens

Liquid & Dust N Rated / AGM020-623-000



DESCRIPTION

Engineered to offer outstanding performance, compatibility and comfort, with the option to fit RX inserts enabling safe use of prescription lenses. Standard single lens goggle for general protection, with EVA foam surround for enhanced comfort and improved fit.

OPTIONS

Liquid & Dust N Rated (AGM020-623-000)

SAFETY STANDARDS

EN 166 • EN 170



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 3 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
2C



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2



Manufacturer's Trademark
JSP Dagger



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T



Protection from Liquid Droplets
3



Protection from Large Dust Particles (up to 40 um grain size)
4



Resistance to Molten Metals and Hot Solids (optional)
9



Resistance to fogging (optional)
N

RX Insert
Optional



Product Weight
100g

FEATURES



Compatibility

Low profile design means the EVO® Goggle can be worn with an industrial safety helmet or bumpcap.



RX Inserts

RX inserts are available for the EVO® Goggle range, for combined prescription and safety eyewear. Inserts can be taken to an optician for glazing with corrective lenses.



Comfort

Foam surround on the goggle housing for comfort and to ensure a good fit across a wide range of facial profiles.

RANGE



DOWNLOADS

[Image Pack \(ZIP\)](#)

[doc-evo-idv-goggle.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 3 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

