

TECHNICAL SPECIFICATION



Jetstream® Industrial Kits

Jetstream® TH2A2P R SL Industrial Kit / CDP030-201-300



DESCRIPTION

Jetstream® is a belt-mounted rechargeable respirator with a large capacity reusable filter supplying filtered air through a highly flexible reinforced hose to a variety of head tops for different applications.

The Jetstream® Industrial Kit carry case contains:

Grinding visor head top

Flexible hose

TH2P R SL dust or TH2A2 P R SL gas and dust filters

Flow meter

Rechargeable battery

Multi-region plug adaptor

OPTIONS

Jetstream® TH2P R SL Industrial Kit (CBP030-001-300)

**Jetstream® TH2A2P R SL Industrial Kit
(CDP030-201-300)**

SAFETY STANDARDS

EN 166 • EN 12941



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 20 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIONS



Manufacturer's Trademark
JSP Dagger



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.

B



Resistance to Molten Metals and Hot Solids (optional)

9

Classification
TH2 (Turbo Hood)

Minimum Filtration Efficiency
98%

Nominal Protection Factor
50

Face Seal Type
Hypoallergenic Material

Latex free
No

Battery Type
8 Hour Rechargeable Nickel Metal Hydride (NiMH)

Noise Level
65dB

Battery Type
8 Hours Rechargeable 6V 4.4 Ah. (NiMH)

Filter Shelf Life
3 Years



Product Weight
Power Pack & TH2A2P R SL Filter 1400g



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



Protection from Liquid Droplets
3



BSI Kitemark
Yes

Usage
R (Reusable)

Maximum Total Inward Leakage (TIL)
2% When Fitted To Jetstream

UK Assigned Protection Factor
20

Mask Design
A Turbo Hood Powered Air Purifying Respirator (Loose Fitting)

Metal Free
No



Product Weight
Head Top 780g

Face Fit Testing Required
No



Filter Type
Organic Vapours, Nuisance Odours and Particulate



Product Weight
TH2A2P R SL Filter 592g

FEATURES



Comfort

Waist mounted blower unit with fully automatic alarm and integrated battery attached to a wide comfortable waist belt.



No Face Fit Testing

As a loose-fitting respirator, Jetstream® is suitable for users with neatly trimmed, well-groomed facial hair and does not require face fit testing.



Comfort

Waist mounted blower unit with fully automatic alarm and integrated battery attached to a wide comfortable waist belt. Complete unit and belt weigh just 765g.




Adaptable

A wide range of kits, filters and head tops are available to suit a variety of tasks.



High Performance

180 litres of air per minute are delivered through the Jetstream® filter via a highly flexible hose to the desired head top.



Easy Cleaning

Quick and easy cleaning; hood, filter housing, blower unit, and hose can be wiped clean with a damp cloth soaked in mild detergent solution.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 20 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





Simple Maintenance

Key components are available as spare parts, enabling simple maintenance and the option to purchase several head tops or filters.





High Performance Filters

TH2A2P R SL (Reusable Organic Gas / Vapour & Solid & Liquid Particulate Aerosol Filter).

RANGE

DOWNLOADS



-  [Image Pack \(ZIP\)](#)
-  [doc-jetstream-industrial-kit.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jssafety.com / Web: www.jssafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jssafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 20 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

