

TECHNICAL SPECIFICATION



Flexinet® Mask FFP2OV (823)

Box of 10 / BER152-201-A00



DESCRIPTION

The Flexinet™ disposable mask has an ergonomic 3D design to fit most face shapes, with extremely low breathing resistance and mesh outer shell to help the mask retain its shape.

- Medium efficiency (94% minimum) filtering.

OPTIONS

Box of 10 (BER152-201-A00)

SAFETY STANDARDS

EN 149



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 17 Jun 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Classification
FFP2 (Filtering Facepiece Particulate)

Usage
'N'R (Non-Reusable)



Activated Carbon Layer
O (Odour Layer)

Maximum Total Inward Leakage (TIL)
8%

UK Assigned Protection Factor
10



Exhalation Valve
Advanced Valve



Nose Bridge
Moulded

Metal Free
Yes

Filter Shelf Life
5 Years



Product Weight
25g



Filter Type
P (Protects Against Solid and Liquid Aerosol)



(D) Resistance to dust clogging
No

Minimum Filtration Efficiency
94% For FFP2 Rated

Nominal Protection Factor
12

Mask Design
Mesh Outer Shell

Toggle Harness adjustment system
Yes


Latex free
Yes

Mask Material
Polypropylene



BSI Kitemark
Yes

FEATURES



Comfort

A 360° comfort foam area around the inside of the mask provides a perfect fit.



Advanced Valve

Advanced design valve allows for lower breathing resistance.



Protective Grill

Flexible cover to protect and retain the shape of the mask and protect the wearer against possible damage to the filter.



Carbon Filter

Features an activated carbon filter layer, providing effective relief from nuisance odours (<WEL) for improved user comfort. Able to block organic and acid gases and vapours with concentrations under the WEL. Ideal for operations with ozone related risks (concentrations under the WEL).

RANGE



DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-olympus-800-series-823.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 17 Jun 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

