

# TECHNICAL SPECIFICATION



## Flexinet® Mask FFP2OV (823)

Box of 10 / BER152-201-A00



### DESCRIPTION

The Flexinet™ disposable mask has an ergonomic 3D design to fit most face shapes, with extremely low breathing resistance and mesh outer shell to help the mask retain its shape.

- Medium efficiency (94% minimum) filtering.

### OPTIONS

**Box of 10 (BER152-201-A00)**

### SAFETY STANDARDS

EN 149



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 17 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Classification  
FFP2 (Filtering Facepiece Particulate)

Usage  
'N'R (Non-Reusable)

Minimum Filtration Efficiency  
94% For FFP2 Rated

Nominal Protection Factor  
12

Mask Design  
Mesh Outer Shell

Toggle Harness adjustment system  
Yes

Latex free  
Yes

Mask Material  
Polypropylene

 BSI Kitemark  
Yes

Face Fit Testing Required  
Yes

 Filter Type  
P (Protects Against Solid and Liquid Aerosol)

 Activated Carbon Layer  
O (Odour Layer)

Maximum Total Inward Leakage (TIL)  
8%

UK Assigned Protection Factor  
10

 Exhalation Valve  
Advanced Valve


 Nose Bridge  
Moulded

Metal Free  
Yes

Filter Shelf Life  
5 Years

 Product Weight  
25g

## FEATURES



### Comfort

A 360° comfort foam area around the inside of the mask provides a perfect fit.



### Advanced Valve

Advanced design valve allows for lower breathing resistance.



### Protective Grill

Flexible cover to protect and retain the shape of the mask and protect the wearer against possible damage to the filter.



### Carbon Filter

Features an activated carbon filter layer, providing effective relief from nuisance odours (<WEL) for improved user comfort. Able to block organic and acid gases and vapours with concentrations under the WEL. Ideal for operations with ozone related risks (concentrations under the WEL).

## RANGE



## DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-olympus-800-series-823.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jgpsafety.com](mailto:sales@jgpsafety.com) / Web: [www.jgpsafety.com](http://www.jgpsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jgpsafety.com](mailto:copyright@jgpsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 17 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

