

TECHNICAL SPECIFICATION



1m Webbing Anchorage Sling

1m Webbing Anchorage Sling / FAR0514



DESCRIPTION

1m webbing anchorage sling made from 20mm wide polyester webbing. 20kN breaking strength.
EN 795 Type B

OPTIONS

1m Webbing Anchorage Sling (FAR0514)

SAFETY STANDARDS

EN 795



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 16 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIONS

Length
1m

Material
20mm Wide Polyester Webbing



Rated Weight / Load
20kN Breaking Strength



Product Weight
110g

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-far0504-far0514.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 16 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

