

# TECHNICAL SPECIFICATION



## 1m Webbing Anchorage Sling

1m Webbing Anchorage Sling / FAR0514



### DESCRIPTION

1m webbing anchorage sling made from 20mm wide polyester webbing. 20kN breaking strength.  
EN 795 Type B

### OPTIONS

**1m Webbing Anchorage Sling (FAR0514)**

### SAFETY STANDARDS

EN 795



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 16 Jul 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Length  
1m



Rated Weight / Load  
20kN Breaking Strength

Material  
20mm Wide Polyester Webbing



Product Weight  
110g

## DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-far0504-far0514.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 16 Jul 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

