TECHNICAL SPECIFICATION

EVOLite® Mid Peak OneTouch™ Slip Ratchet Vented

Blue / AJB160-000-500



DESCRIPTION

The EVOLite® is a breakthrough product enabling Health and Safety Officers to achieve new levels of compliance due to its unrivalled comfort. It is lightweight, extremely comfortable and fits the widest range of head shapes and sizes. The harness and shell are truly integrated as one to give the best performance by keeping it firmly rooted on the head, even when fully inverted.

OPTIONS

Black (AJB160-001-100)

Blue (AJB160-000-500)

Green (AJB160-000-300)

Grey (AJB160-000-400)

Orange (AJB160-000-800)

Red (AJB160-000-600)

White (AJB160-000-100)

Yellow (AJB160-000-200)

SAFETY STANDARDS

EN 397

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Peak
Mid

Lateral Deformation
Yes

Maximum Temperature
+50˚C

ABS Shell
Yes

Textile
Harness

Slip Ratchet
Slip

Ventilation
Yes

Integrated Eyewear
Optional

BSI Kitemark
Yes

Optional 4 point chinstrap (EN397 Compliant)
Optional

Product Weight
328g

Impact Resistance
50 Joules

Resistance to Molten Metals and Hot Solids (optional)
Yes

Minimum Temperature
-40˚C

Recyclable
Shell

Depth Adjustment
3D Harness

Universal Accessories Slot
Yes

Reflective Option
Optional


ID card holder
Optional

Optional 2 point chinstrap (EN397 & EN 812 compliant)
Optional

JSPCheck
Yes

Size
53-64cm

FEATURES



Supreme Comfort

A 6-point textile cradle harness system & Chamlon™ cotton sweatband offer unrivalled comfort.




Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. Available with either the Revolution® Flex wheel ratchet or the OneTouch™ slip ratchet.



Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors, and ear defenders. EVOSpec® Integrated eyewear is also available.



Ventilation Option

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.



3D Adjustment

The textile harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.



CR2™ Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility / reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

LOGO

- [x] Front
- [x] Back
- [x] Sides

RANGE

VIDEOS

- www.youtube.com/watch?v=r9zutN49DO25
- www.youtube.com/watch?v=LdxMNctXLbg
- www.youtube.com/watch?v=4iv_k1SEs4g
- www.youtube.com/watch?v=WXD2v6an1as&t

DOWNLOADS

- Image Pack (ZIP)
- doc-invincible-evolite.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.