

TECHNICAL SPECIFICATION



EVOGuard®M Forestry Browguard Systems

EVOGuard®M3 Forestry Browguard System / ADB28A-400-800



DESCRIPTION

The EVOGuard® M Forestry browguard and helmet systems are innovative solutions to protect the wearer in a multitude of high risk working environments. All EVOGuard® visor components are fully compatible with a range of existing EVO® helmet models.

OPTIONS

EVOGuard®M2 Forestry Browguard System
(ADB28A-300-800)

**EVOGuard®M3 Forestry Browguard System
(ADB28A-400-800)**

SAFETY STANDARDS

EN 1731 • EN 352-3 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.















Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.


Page 1 of 3 / Issued 15 Sep 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.



SPECIFICATIONS

	Harness 6 Point Multi-Position Adjustment/Fitting System		Universal Accessories Slot Yes
	Wheel Ratchet Yes		Integrated Eyewear Fitted
	Manufacturer's Trademark JSP Dagger		Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s [°] Maximum protection for glasses F
	Visible Light Transmittance (VLT) 80%		Visor Length 18cm
	Mounting Browguard/Helmet		SNR 31 dB
	Adjustable Yes		BSI Kitemark Yes
	JSPCheck Yes		Material 30% Glass Filled Nylon Browguard
	Material ABS Frame and Chemically Etched Stainless Steel Mesh		Material ABS/Stainless Steel Wire
	Recyclable Yes		Product Weight 605g

FEATURES



Visor Range

Two high performance complete forestry systems are available, enabling users to select the perfect visor for their task and price point.



Dual Layer Protection

The EVOGuard®M Forestry Helmet and Forestry Browguard Systems both feature a secondary layer of eye protection in the form of the integrated EVOSpec® polycarbonate retractable eyeshield.



Supreme Comfort

Features an easy to use Revolution® wheel ratchet and a 3D-Adjustment harness, which offers 1-2-3 point depth settings for increased adaptability to ensure a perfect, secure fit.



Supreme Comfort & Fit

Features the new JSP Revolution® wheel ratchet, securely tightening and holding the unit firmly in position, no matter the task or amount of user movement involved. System comes complete with a wraparound, soft foam backed, replaceable, Chamlon™ sweatband offers superior comfort.



Balanced & Secure

Fitted to a browguard or helmet, the self-lubricating nylon hinges hold the visor securely in position even during extreme movement, whilst offering balanced, even weight distribution.



Product Compatibility

Designed to maximise compatibility with a broad range of JSP products, such as the Force®8 respirator with PressToCheck™, Springfit™ disposable masks and the Sonis® helmet mounted ear defender range.



Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement or vision.



Maximum Adjustability

Multiple fitting positions allow the wearer to adjust the browguard in three ways. An over the crown slide fitting combined with a forward and back adjustment, maximises compatibility with different head shapes.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.


Page 2 of 3 / Issued 15 Sep 2025 / Copyright 2018 - 2025, JSP Limited. All Rights Reserved.





High Quality Materials

The EVOGuard®M3 Forestry Visor is comprised of an ABS over-moulded frame with an etched stainless steel visor material.



Visible Light Transmittance

The EVOGuard®M3 Forestry Visor offers 80% visible light transmittance.



Impact Protection

The EVOGuard®M3 Forestry Visor features an F - Impact rating, offering increased impact resistance when fitted to a EVOGuard®M Forestry browguard or helmet unit.

RANGE



DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-evoguard.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 15 Sep 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

