

# TECHNICAL SPECIFICATION



## EVOGuard®M Forestry Browguard Systems

EVOGuard®M2 Forestry Browguard System / ADB28A-300-800



### DESCRIPTION

The EVOGuard® M Forestry browguard and helmet systems are innovative solutions to protect the wearer in a multitude of high risk working environments. All EVOGuard® visor components are fully compatible with a range of existing EVO® helmet models.

### OPTIONS

**EVOGuard®M2 Forestry Browguard System  
(ADB28A-300-800)**

EVOGuard®M3 Forestry Browguard System  
(ADB28A-400-800)

### SAFETY STANDARDS

EN 1731 • EN 352-3 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.
















Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.


Page 1 of 3 / Issued 19 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

 <p>Harness 6 Point Multi-Position Adjustment/Fitting System</p>	 <p>Universal Accessories Slot Yes</p>
 <p>Wheel Ratchet Yes</p>	 <p>Integrated Eyewear Fitter</p>
 <p>Manufacturer's Trademark JSP Dagger</p>	 <p>Increased Robustness resists a 22mm, 43g steel ball travelling at 5.1 metres per second. This is derived from the practical test which is to drop the ball (as stipulated) from a height of 1.3 metres.</p>
 <p>Visible Light Transmittance (VLT) 70%</p>	 <p>S</p>
 <p>Mounting Browguard/Helmet</p>	 <p>Visor Length 18cm</p>
<p>Adjustable Yes</p>	 <p>SNR 31 dB</p>
 <p>JSPCheck Yes</p>	 <p>BSI Kitemark Yes</p>
<p>Material ABS Frame and Woven Stainless Steel Mesh</p>	<p>Material 30% Glass Filled Nylon Browguard</p>
 <p>Recyclable Yes</p>	<p>Material ABS/Stainless Steel Wire</p>
	 <p>Product Weight 605g</p>

## FEATURES



### Visor Range

Two high performance complete forestry systems are available, enabling users to select the perfect visor for their task and price point.



### Dual Layer Protection

The EVOGuard®M Forestry Helmet and Forestry Browguard Systems both feature a secondary layer of eye protection in the form of the integrated EVOSpec® polycarbonate retractable eyeshield.



### Supreme Comfort

Features an easy to use Revolution® wheel ratchet and a 3D-Adjustment harness, which offers 1-2-3 point depth settings for increased adaptability to ensure a perfect, secure fit.



### Supreme Comfort & Fit

Features the new JSP Revolution® wheel ratchet, securely tightening and holding the unit firmly in position, no matter the task or amount of user movement involved. System comes complete with a wraparound, soft foam backed, replaceable, Chamlon™ sweatband offers superior comfort.



### Balanced & Secure

Fitted to a browguard or helmet, the self-lubricating nylon hinges hold the visor securely in position even during extreme movement, whilst offering balanced, even weight distribution.



### Product Compatibility

Designed to maximise compatibility with a broad range of JSP products, such as the Force®8 respirator with PressToCheck™, Springfit™ disposable masks and the Sonis® helmet mounted ear defender range.



### Coverage

EVOGuard® visors provide comprehensive facial coverage without limiting movement or vision.



### Maximum Adjustability

Multiple fitting positions allow the wearer to adjust the browguard in three ways. An over the crown slide fitting combined with a forward and back adjustment, maximises compatibility with different head shapes.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 19 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





### High Quality Materials

The EVOGuard®M2 Forestry Visor is comprised of an ABS over-moulded frame with a woven stainless steel visor material.



### Visible Light Transmittance

The EVOGuard®M2 Forestry Visor offers 70% visible light transmittance.



### Impact Protection


The EVOGuard®M2 Forestry Visor features an S - Impact rating, offering increased impact resistance when fitted to a EVOGuard®M Forestry browguard or helmet unit.'

## RANGE

## DOWNLOADS



 [Image Pack \(ZIP\)](#)

 [doc-evoguard.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 19 Jun 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

