

# TECHNICAL SPECIFICATION



## EVO®3 Mid Peak OneTouch™ Slip Ratchet Vented

Yellow / AJF160-000-200



### DESCRIPTION

The EVO®3 Comfort Plus helmet combines a super strong shell for superior all day protection in the widest range of environments, with the comfort benefits of the new Evolution® 3D Adjustment™ harness system. EVO®3 is a true evolution of the long-established MK®2 and MK®3 helmets. The EVO®3 retains the JSP signature styling while incorporating developments first seen in the EVO®8. Packed full of the latest protection technology and features.

### OPTIONS

Black (AJF160-001-100)  
Blue (AJF160-000-500)  
Green (AJF160-000-300)  
Grey (AJF160-000-400)  
Orange (AJF160-000-800)  
Pink (AJF160-003-900)  
Red (AJF160-000-600)  
White (AJF160-000-100)  
**Yellow (AJF160-000-200)**

### SAFETY STANDARDS

EN 397



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.






















Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 20 Sep 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.



## SPECIFICATIONS

|  |  |  |  |
|--|--|--|--|
|    | Peak<br>Mid  |   | Impact Resistance<br>50 Joules                           |
|    | Resistance to Molten Metals and Hot Solids Helmets (optional)<br>Yes |   | Maximum Temperature<br>+50°C                             |
|    | Minimum Temperature<br>-40°C   |   | HDPE Shell<br>Yes  |
|    | Recyclable<br>Shell  |   | Textile<br>Harness                                       |
|    | Depth Adjustment<br>3D Harness                                       |   | Slip Ratchet<br>Slip                                     |
|    | Universal Accessories Slot<br>Yes                                    |   | Ventilation<br>Yes                                       |
|    | Reflective Option<br>Optional  |   | Integrated Eyewear<br>Optional                           |
|    | ID card holder<br>Optional   |   | BSI Kitemark<br>Yes                                      |
|    | Optional 2 point chinstrap (EN397 & EN 812 compliant)<br>Optional    |   | Optional 4 point chinstrap (EN397 Compliant)<br>Optional |
|   | JSPCheck<br>Yes  |  | Product Weight<br>372g                                   |
|  | Size<br>53-64cm  |  |  |

## FEATURES



### Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. Available with either the Revolution® wheel ratchet or the OneTouch™ slip ratchet.



### CR2™ Reflective

Using Class RA2, high intensity reflective. CR2™ is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



### Supreme Comfort

A 6-point textile cradle harness system & Chamlon™ cotton sweatband offer unrivalled comfort.



### 3D Adjustment

The comfortable textile harness features unique 1-2-3 point depth settings, offering the most precise fit attainable on an industrial safety helmet.



### Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors and ear defenders. EVOSpec® Integrated eyewear is also available.



### JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



### Ventilation Option

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 20 Sep 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.



## APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Agricultural

Airports

Construction and Infrastructure

Maritime

Oil, Gas and Chemical Companies

Scaffolding and Roofing

Sole Trader

Utilities Contractors

## LOGO

- Front
- Back
- Sides

## RANGE



## VIDEOS

- [www.youtube.com/watch?v=PmDMMktdotQ](http://www.youtube.com/watch?v=PmDMMktdotQ)
- [www.youtube.com/watch?v=LdxMNctXLbg](http://www.youtube.com/watch?v=LdxMNctXLbg)

## DOWNLOADS

- [Image Pack \(ZIP\)](#)
- [doc-invincible-evo3.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 20 Sep 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

