

# TECHNICAL SPECIFICATION



## EVO®3 Mid Peak Revolution® Wheel Ratchet Vented

White / AJF170-000-100



### DESCRIPTION

The EVO®3 Comfort Plus helmet combines a super strong shell for superior all day protection in the widest range of environments, with the comfort benefits of the new Evolution® 3D Adjustment™ harness system. EVO®3 is a true evolution of the long-established MK®2 and MK®3 helmets. The EVO®3 retains the JSP signature styling while incorporating developments first seen in the EVO®8. Packed full of the latest protection technology and features.

### OPTIONS

Black (AJF170-001-100)  
Blue (AJF170-000-500)  
Green (AJF170-000-300)  
Orange (AJF170-000-800)  
Red (AJF170-000-600)  
**White (AJF170-000-100)**  
Yellow (AJF170-000-200)

### SAFETY STANDARDS

EN 397



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.






















Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 27 Jul 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

	Peak Mid		Size 53-64cm
	Resistance to Molten Metals and Hot Solids Helmets (optional) Yes		Minimum Temperature -40°C
	Maximum Temperature +50°C		HDPE Shell Yes
	Recyclable Shell		Textile Harness
	Depth Adjustment 3D Harness		Wheel Ratchet Yes
	Universal Accessories Slot Yes		Ventilation Yes
	Reflective Option Optional		Integrated Eyewear Optional
	ID card holder Optional		BSI Kitemark Yes
	Optional 2 point chinstrap (EN397 & EN 812 compliant) Optional		Optional 4 point chinstrap (EN397 Compliant) Optional
	JSPCheck Yes		Product Weight 372g
	Size 53-64cm		

## FEATURES



### Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. Available with either the Revolution® wheel ratchet or the OneTouch™ slip ratchet.



### CR2™ Reflective

Using Class RA2, high intensity reflective. CR2™ is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



### Supreme Comfort

A 6-point textile cradle harness system & Chamlon™ cotton sweatband offer unrivalled comfort.



### 3D Adjustment

The comfortable textile harness features unique 1-2-3 point depth settings, offering the most precise fit attainable on an industrial safety helmet.



### Accessories

A universal attachment slot enables firm fitting of a range of Surefit™ safety visors and ear defenders. EVOSpec® Integrated eyewear is also available.



### JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



### Ventilation Option

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 27 Jul 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



## APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Agricultural

Airports

Construction and Infrastructure

Maritime

Oil, Gas and Chemical Companies

Scaffolding and Roofing

Sole Trader

Utilities Contractors

## LOGO

- Front
- Back
- Sides

## RANGE



## VIDEOS

- [www.youtube.com/watch?v=PmDMMktdotQ](http://www.youtube.com/watch?v=PmDMMktdotQ)
- [www.youtube.com/watch?v=LdxMNctXLbg](http://www.youtube.com/watch?v=LdxMNctXLbg)

## DOWNLOADS

- [Image Pack \(ZIP\)](#)
- [doc-invincible-evo3.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 27 Jul 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

