TECHNICAL SPECIFICATION



EVO®3 Mid Peak Revolution® Wheel Ratchet Vented

White / AJF170-000-100



DESCRIPTION

The EVO®3 Comfort Plus helmet combines a super strong shell for superior all day protection in the widest range of environments, with the comfort benefits of the new Evolution® 3D Adjustment[™] harness system. EVO®3 is a true evolution of the long-established MK®2 and MK®3 helmets. The EVO®3 retains the JSP signature styling while incorporating developments first seen in the EVO®8. Packed full of the latest protection technology and features.

OPTIONS

Black (AJF170-001-100) Blue (AJF170-000-500) Green (AJF170-000-300) Orange (AJF170-000-800) Red (AJF170-000-600) White (AJF170-000-100) Yellow (AJF170-000-200)

SAFETY STANDARDS

EN 397



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



SPECIFICATIONS



Peak Mid Resistance to Molten Metals and Hot Solids (optional) Yes Maximum Temperature +50°C Recyclable Shell Depth Adjustment **3D Harness** Universal Accessories Slot Yes **Reflective Option** Optional ID card holder ≗ Optional Optional 2 point chinstrap (EN397 & EN 812 compliant) Optional JSPCheck



Size 53-64cm

Yes

FEATURES



Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. Available with either the Revolution® wheel ratchet or the OneTouch™ slip ratchet.



CR2™ Reflective

Using Class RA2, high intensity reflective. CR2™ is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



Supreme Comfort

A 6-point textile cradle harness system & Chamlon[™] cotton sweatband offer unrivalled comfort.



Ventilation Option

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.



Size

53-64cm

-40°C

Yes

Textile

Yes

Yes

Yes

Harness

Ventilation

Optional

Optional

372g

Product Weight

BSI Kitemark

Wheel Ratchet

Integrated Eyewear

HDPE Shell

Minimum Temperature

ᠿ

HDPE

3D Adjustment

Optional 4 point chinstrap (EN397 Compliant)

The comfortable textile harness features unique 1-2-3 point depth settings, offering the most precise fit attainable on an industrial safety helmet.

Accessories

A universal attachment slot enables firm fitting of a range of Surefit[™] safety visors and ear defenders. EVOSpec® Integrated eyewear is also available.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



LOGO RANGE ✓ Front ✓ ✓ Back ✓ ✓ Sides DOWNLOADS

- www.youtube.com/watch?v=PmDMMktdotQ
- www.youtube.com/watch?v=LdxMNctXLbg

- Image Pack (ZIP)
- doc-invincible-evo3.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.