

Thermex™ bril met dubbele lens

Standaard / AGM020-723-000



BESCHRIJVING

Met een buitenlens van polycarbonaat en een binnenlens van acetaat biedt de Thermex™ goggle ongeëvenaarde anticondens prestaties in extreme omgevingen. De unieke Thermex™ Moisture Control Patch compenseert luchtdrukopbouw veroorzaakt door hitte of hoogte. De bril heeft NBR-schuimranden voor meer comfort en een betere pasvorm.

OPTIES

Standaard (AGM020-723-000)

VEILIGHEIDSNORMEN

EN 166 • EN 170



SPECIFICATIES



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
2C



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1,2



Manufacturer's Trademark
JSP Dolk



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles.
B



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T



Protection from Liquid Droplets
3



Protection from Large Dust Particles (up to 40 um grain size)
4



Resistance to Molten Metals and Hot Solids Helmets (optional)
9



Resistance to Surface Damage by Fine Particles (optional)
K



Resistance to fogging (optional)
N

Lens Material
Polycarbonaat buitenlens - Acetaat binnenlens

RX Insert
Optioneel

Material
afdichtingsmateriaal NBR - nitrilbutadiëenrubber



Product Weight
107g

KENMERKEN



Dubbele lensbescherming

Medium energie (B-klasse) impact bij extreme temperaturen, met aanvullende tests uitgevoerd bij -40°C.



Mistvrij zicht

De unieke Thermex™ Moisture Control Patch compenseert luchtdrukopbouw veroorzaakt door hitte of hoogte om vervormingsvrij optisch klasse 1-zicht te garanderen.



Comfort

NBR-schuim op de behuizing van de bril zorgt voor een comfortabele pasvorm voor een breed scala aan gezichtsprofielen.

BEREIK

DOWNLOADS

THERMEX™

[Pakket afbeeldingen \(ZIP\)](#)

[doc-evo-thermex-goggle.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 11 Feb 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

