TECHNICAL SPECIFICATION



Mk®7.0

*MK®7.0 Long Peak Vented White Helmet - Wheel Ratchet - Large Vents - LED Lamp Bracket + LED Lamp / AHO171-J00-100



DESCRIPTION

Mk®7.0 features classic shell design with rain channel. Available with three ventilation options and offering compatibility with EVO® accessories and a range of other JSP PPE, the Mk®7.0 provides the latest performance while retaining the styling of traditional industrial safety helmets.

OPTIONS

MK®7.0 Long Peak White Helmet - Wheel Ratchet (AHM170-000-100)

MK®7.0 Long Peak White Helmet - Wheel Ratchet - 3Pt Lamp Bracket + Cable Loop (AHM179-300-100)

MK®7.0 Long Peak Vented White Helmet - Wheel Ratchet (AHN170-000-100)

MK®7.0 Long Peak Vented White Helmet - Wheel Ratchet - Large Vents (AHO170-000-100)

*MK®7.0 Long Peak Vented White Helmet - Wheel Ratchet - Large Vents - LED Lamp Bracket + LED Lamp (AHO171-J00-100)

SAFETY STANDARDS

EN 397



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



SPECIFICATIONS



Peak Standard



Resistance to Molten Metals and Hot Solids (optional) Yes



-40°C

Recyclable Yes



Depth Adjustment **3D Harness**



Universal Accessories Slot Yes

Minimum Temperature



BSI Kitemark Yes

393g (Approx)



Optional 4 point chinstrap (EN397 Compliant) Optional **Product Weight**



EN 50365 ELECTRICAL INSULATION None

FEATURES



Strength And Comfort

The Mk®7.0 helmet features a super-strong HDPE shell combined with Revolution® wheel ratchet harness and Chamlon™ sweatband for maximum comfort and perfect fit.



Classic Design

The Mk®7.0 classic shell design features a rain channel around the brim, distinctive JSP shield, and raised 'stripe' on the crown.



Accessories

The Mk®7.0 is also compatible with EVO® helmet accessories, including thermal liners, neck capes, and chinstraps. Lamp brackets and cable loops are available as factory-fitted options.



Impact Resistance 50 Joules



Maximum Temperature +50°C



Textile Harness



Wheel Ratchet Yes



Integrated Eyewear Optional



Optional 2 point chinstrap (EN397 & EN 812 compliant) Optional



JSPCheck Yes



Size 53-64cm

Ventilation Yes - Large Vent



3D Adjustment

The textile harness features unique 1-2-3-point depth settings. This offers the most precise fit attainable on a safety helmet.



Ventilation Options

Available with three ventilation options: nonvented, small vented, or large vented. Non-vented and small vent options provide electrical insulation up to 1000V, or choose large vents for optimal coolness and comfort.



Bespoke Your Mk®7.0

Strengthen corporate identity by applying a company logo to the Mk®7.0 safety helmet using the JSP Logo Express® service. Minimum order quantities and set-up charges apply.

LOGO

Front

- Sides
- Back



Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



RANGE







DOWNLOADS

- Image Pack (ZIP)
- doc-helmets-mk-7.0.pdf (PDF)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

