

TECHNICAL SPECIFICATION



EVO®2 Mid Peak OneTouch™ Slip Ratchet Non Vented

White / AJE030-000-100



DESCRIPTION

The EVO®2 Comfort Plus helmet combines a super strong shell for superior all day protection in the widest range of environments, with the comfort benefits of the new Evolution® 3D Adjustment™ harness system. EVO®2 is a true evolution of the long-established MK®2 and MK®3 helmets. The EVO®2 retains the JSP signature styling while incorporating developments first seen in the EVO®8. Packed full of the latest protection technology and features.

OPTIONS

Black (AJE030-001-100)
Blue (AJE030-000-500)
Green (AJE030-000-300)
Grey (AJE030-000-400)
Orange (AJE030-000-800)
Red (AJE030-000-600)
White (AJE030-000-100)
Yellow (AJE030-000-200)

SAFETY STANDARDS

EN 397 • EN 50365



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.





















Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 2 Aug 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS

	Impact Resistance 50 Joules		EN 50365 ELECTRICAL INSULATION 1000V
	EN 50365 ELECTRICAL INSULATION 440 V		Resistance to Molten Metals and Hot Solids (optional) Yes
	Maximum Temperature +50°C		Minimum Temperature -30°C
	HDPE Shell Yes		Recyclable Shell
	LDPE Harness Yes		Depth Adjustment 3D Harness
	Slip Ratchet Slip		Peak Mid
	Universal Accessories Slot Yes		Ventilation No
	BSI Kitemark Yes		Reflective Option Yes
	ID card holder Optional		JSPCheck Yes
	Product Weight 402g		Size 53-64cm

FEATURES



Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. The OneTouch™ slip ratchet makes it simple to tighten to the perfect fit.



CR2 Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



Supreme Comfort

A traditional 6-point polyethylene harness making the EVO®2 the more economical choice, whilst still providing the same high performance as the EVO®3.



3D Adjustment

The polyethylene harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.



Accessories

Universal attachment slot enables firm fitting of a range of safety visors and ear defenders.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.

LOGO

- ☒ Front
- ☒ Back
- ☒ Sides

RANGE



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 2 Aug 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



VIDEOS

 www.youtube.com/watch?v=PmDMMktdotQ

DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-invincible-evo2.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 2 Aug 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

