

ESPECIFICACIONES TÉCNICAS



Eslinga de anclaje de cincha de 2 m

Eslinga de anclaje de cincha de 2 m / FAR0504



DESCRIPCIÓN

Eslinga de anclaje de 2 m hecha de correas de poliéster de 20 mm de ancho. Resistencia a la rotura 25KN

OPCIONES

Eslinga de anclaje de cincha de 2 m (FAR0504)

NORMAS DE SEGURIDAD

EN 795



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 29 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



ESPECIFICACIONES

Longitud
2m

Material
Correas de poliéster de 20 mm de ancho



Peso/carga nominal
Resistencia a la rotura 20kn



Peso del producto
250g

DESCARGAR

 [Colección de imágenes \(ZIP\)](#)

 [doc-far0504-far0514.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 29 May 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

