TECHNICAL SPECIFICATION



Swiss One LEONE

1LEO23C / 1LEO23C



DESCRIPTION

Elegance & performance to deliver an optimal safety spectacle. Perfectly contoured for optimal fit without pressure.

A 9 base curve providing excellent side coverage and maximum peripheral vision. Forget safety, enjoy the fit and features of stylish protective eyewear!

OPTIONS

1LEO21SVAR (1LEO21SVAR)

1LEO23C (1LEO23C)

1LEO23S (1LEO23S)

1LEOCARB21SPOL (1LEOCARB21SPOL)

1LEOCARB23S (1LEOCARB23S)

SAFETY STANDARDS

EN 170 • EN 166





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect Scale Number

2C



Manufacture's Trademark Swiss One

Swiss One



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s ° Maximum protection for glasses



Resistance to Surface Damage by Fine Particles (optional)

Exellence Coating (KN Anti-Scratch/Anti-Mist)

Yes

Lightweight

Yes

Soft End Tips - Flex Flat Temple Pressure Free

Yes



LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2



Optical Class (1 - Class 1 - High quality for regular use. 2 -Class 2 - Medium quality for occasional use. 3 - Class 3 -Low quality for exceptional use)



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional

Т



Resistance to fogging (optional)

Ν

Lens Base Curve

Soft Nose Pad

Yes



Product Weight

24g

FEATURES





Anti-mist

Anti-mist





UV 400 Absorption

UV 400 absorption





High Performance Coating

Anti-scratch / anti-fog high performance coating





Soft Nose Pad

Soft nose pad





Anti-scratch

Anti-scratch





Lens Curve

Lens curve





Lightweight

Lightweight





Soft End Tips

Soft end tips

RANGE



DOWNLOADS



Image Pack (ZIP)



doc-leone.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





