

## Swiss One LEONE

1LEO23C / 1LEO23C



### DESCRIPTION

Élégance, performance...le tout pour vous offrir une sécurité optimale. Un compromis de technologie, de design et de confort. Le style d'une lunette métal, le confort d'une lunette légère. Une courbe exceptionnelle offrant une couverture parfaite et sans pression, un pont nasal souple et mobile. Quand la protection devient plaisir .

### OPTIONS

1LEO21SVAR (1LEO21SVAR)  
**1LEO23C (1LEO23C)**  
1LEO23S (1LEO23S)  
1LEOCARB21SPOL (1LEOCARB21SPOL)  
1LEOCARB23S (1LEOCARB23S)

### NORMES

EN 170 • EN 166



## INFORMATIONS TECHNIQUES



RADIATION PROTECTION BREAKDOWN filtering effect  
Scale Number  
2C



Manufacture's Trademark Swiss One  
**Swiss One**



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °  
Maximum protection for glasses  
**F**



Resistance to Surface Damage by Fine Particles (optional)  
**K**

Excellence Coating (KN Anti-Scratch/Anti-Mist)  
**Oui**

Lightweight  
**Oui**

Soft End Tips - Flex Flat Temple Pressure Free  
**Oui**



LIGHT TRANSMISSION BREAKDOWN Lens Shade number  
1,2



Optical Class (1 – Class 1 – High quality for regular use. 2 –  
Class 2 – Medium quality for occasional use. 3 – Class 3 –  
Low quality for exceptional use)  
**1**



The letter T, immediately after the mechanical strength  
symbol, authorises use for high speed particles at extreme  
temperatures. (-5°C and +55°C) Optional  
**T**



Resistance to fogging (optional)

Lens Base Curve  
**9**

Soft Nose Pad  
**Oui**



Product Weight  
**24g**

## CARACTÉRISTIQUES



### anti-buée

anti-buée



### Absorption des rayons UV 400

Absorption des rayons UV 400



### Revêtement haute performance

Revêtement haute performance anti-rayures / anti-  
buée



### Pont nasal souple

Pont nasal souple



### Anti-scratch

Anti-scratch



### Courbe de l'oculaire

Courbe de l'oculaire



### Léger

Léger



### Embouts souples

Embouts souples

## GAMME



## TÉLÉCHARGEMENTS

[Pack d'images \(ZIP\)](#)

[doc-leone.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 22 Jan 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

