

## Swiss One LEONE

1LEO23C / 1LEO23C



### OPIS

Elegancja i wydajność, aby zapewnić optymalne bezpieczeństwo. Idealnie wyprofilowane dla optymalnego dopasowania bez ucisku. Krzywa bazowa 9-tego stopnia zapewnia doskonałe pokrycie boczne i maksymalne widzenie peryferyjne. Zapomnisz, że to okulary ochronne, ciesz się dopasowaniem i funkcjami stylowych okularów, okularów ochronnych!

### OPCJE

1LEO21SVAR (1LEO21SVAR)  
**1LEO23C (1LEO23C)**  
1LEO23S (1LEO23S)  
1LEOKARB21SPOL (1LEOCARB21SPOL)  
1LEOKARB23S (1LEOCARB23S)

### NORMY BEZPIECZEŃSTWA

EN 170 • EN 166



## SPECYFIKACJE



RADIATION PROTECTION BREAKDOWN filtering effect  
Scale Number  
2C



Manufacturer's Trademark Swiss One  
**Swiss One**



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °  
Maximum protection for glasses  
**F**



Resistance to Surface Damage by Fine Particles (optional)  
**K**

Excellence Coating (KN Anti-Scratch/Anti-Mist)  
**Tak**

Lightweight  
**Tak**

Soft End Tips - Flex Flat Temple Pressure Free  
**Tak**



LIGHT TRANSMISSION BREAKDOWN Lens Shade number  
1,2



Optical Class (1 – Class 1 – High quality for regular use. 2 –  
Class 2 – Medium quality for occasional use. 3 – Class 3 –  
Low quality for exceptional use)  
**1**



The letter T, immediately after the mechanical strength  
symbol, authorises use for high speed particles at extreme  
temperatures. (-5°C and +55°C) Optional  
**T**



Resistance to fogging (optional)

Lens Base Curve  
**9**

Soft Nose Pad  
**Tak**



Product Weight  
**24g**

## CECHY



### Nieparujące



Nieparujące



### Absorpcja promieni UV 400



Absorpcja promieni UV 400



### Powłoka o wysokiej wydajności



Powłoka nierysująca / nieparująca o wysokiej  
wydajności



### Miękki mostek nosowy



Miękki mostek nosowy



### Nierysujące



Nierysujące



### Krzywizna soczewki



Krzywizna soczewki



### Lekkie



Lekkie



### Miękkie końcówki



Miękkie końcówki

## GAMA



## PLIKI DO POBRANIA

[Zbiór zdjęć \(ZIP\)](#)

[doc-leone.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 22 Jan 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

