TECHNISCHE SPEZIFIKATION

Powercap® IP Ersatz-Gesichtsabdichtung

Standard / CAU071-001-100



BESCHREIBUNG

Ersatz-Dichtung, um die PowerCap® Active™ IP dicht zu halten und ein optimales Maß an Schutz zu bieten. Dieses Produkt gilt nur für die IP-Serie mit Aufprallschutz (IP).

OPTIONEN

Standard (CAU071-001-100)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPEZIFIKATIONEN

Ersatzteile
Gesichtsabdichtung IP

EIGENSCHAFTEN



Powered Air

Protection to EN 12941 TH1P provides a cooling, comfortable supply of filtered air at 160 litres per minute, eliminating breathing resistance and visor misting.



Micro USB Charging

PowerCap® Active™ is supplied with a micro USB cable for recharging in as little as 5 hours. The PowerBox™1 battery pack features a built-in fuel gauge, making it easy to check charge level.



Kopfschutz durch Anstoßkappe

The cap uses JSP HardCap™ A1+ bump cap technology, exceeding the EN 812 standard. The cap cover is easily removable, wipeable and machine washable.

SERIE

POWERCAP Active

VIDEOS

youtu.be/0yFoliUPusM

DOWNLOADS

Bilderordner (ZIP)
doc-powercap_active_ip.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.