

# TECHNICAL SPECIFICATION



## Flexinet® Mask FFP2V (822)

Box of 10 / BER122-201-A00



### DESCRIPTION

The Flexinet™ disposable mask has an ergonomic 3D design to fit most face shapes, with extremely low breathing resistance and mesh outer shell to help the mask retain its shape.

- Medium efficiency (94% minimum) filtering.

### OPTIONS

**Box of 10 (BER122-201-A00)**

### SAFETY STANDARDS

EN 149



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 17 Jun 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Classification  
FFP2 (Filtering Facepiece Particulate)

Usage  
NR (Non-Reusable)



Activated Carbon Layer  
No

Maximum Total Inward Leakage (TIL)  
8%

UK Assigned Protection Factor  
10



Exhalation Valve  
Advanced Valve



Nose Bridge  
Moulded

Metal Free  
Yes

Filter Shelf Life  
5 Years



Product Weight  
22g



Filter Type  
P (Protects Against Solid and Liquid Aerosol)



(D) Resistance to dust clogging  
Yes – D marking = passes optional clogging test

Minimum Filtration Efficiency  
94% For FFP2 Rated

Nominal Protection Factor  
12

Mask Design  
Mesh Outer Shell

Toggle Harness adjustment system  
Yes


Latex free  
Yes

Mask Material  
Polypropylene



BSI Kitemark  
Yes

## FEATURES



### Comfort

A 360° comfort foam area around the inside of the mask provides a perfect fit.



### Advanced Valve

Advanced design valve allows for lower breathing resistance.



### Protective Grill

Flexible cover to protect and retain the shape of the mask and protect the wearer against possible damage to the filter.

## RANGE



## DOWNLOADS

 [Image Pack \(ZIP\)](#)

 [doc-olympus-800-series-822.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 17 Jun 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

