TECHNICAL SPECIFICATION



PressToCheck™ P3 Dust Filters

Pack of 2 / BMN990-001-700



DESCRIPTION

PressToCheck™ is the easiest way to face-fit check the seal of your respirator, every time you put it on! The range features HEPA filtration exceeding 99.97%, Low profile design maximising compatibility and low breathing resistance across the range.

F-4003 P3 dust encapsulated filters, featuring PressToCheck™ technology for daily face-fit reassurance.

Winner of the BSIF Product Innovation Award.

OPTIONS

Pack of 2 (BMN990-001-700)

SAFETY STANDARDS

EN 143















SPECIFICATIONS

Classification

P3

Usage

R (Reusable)

Activated Carbon Layer

No

Minimum Filtration Efficiency

99.97% To NIOSH Standard For P100 Filter

Maximum Total Inward Leakage (TIL)

0.05% when fitted to a Force10 Full Face Mask

Nominal Protection Factor

1000 When Fitted To A Force10 Full Face Mask

UK Assigned Protection Factor

40 When Fitted To A Force10 Full Face Mask

Latex free

Yes

Filter Material

Pleated Media

Filter Shelf Life

10 Years

Overall Product Weight

92g Per Pair

Filter Type

P (Protects Against Solid and Liquid Aerosols)

(D) Resistance to dust clogging

Yes - mandatory test in EN 143

Minimum Filtration Efficiency

99.95%

Maximum Total Inward Leakage (TIL) 2% when fitted to Force8 Half Mask

Nominal Protection Factor

48 When Fitted To A Force8 Half Mask

UK Assigned Protection Factor

20 When Fitted To A Force8 Half Mask

Type

Press To Check Technology

Metal Free

Yes

Filter Casing Material

ABS

BSI Kitemark

Yes

FEATURES



Increased Product Life

PressToCheck™ encapsulated filters offer ultimate longevity – the durable design makes the filters easy to clean and reuse. Correct cleaning, maintenance and storage increases the useful life of the product.

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Construction and Infrastructure

Manufacturing

VIDEOS

- youtu.be/1Y9G8E9kEXQ
- youtu.be/Ecyu_ftPPX4
- youtu.be/-oUSyP9_NsA

DOWNLOADS

Image Pack (ZIP)

doc-force-press-to-check-filter-f-4003.pdf (PDF)





JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com





