

TECHNICAL SPECIFICATION



Swiss One COVERLITE

1COV23C / 1COV23C



DESCRIPTION

COVERLITE one of the best definition of a Creative eyewear... overspecs for prescription wearers or spectacle for visitors whatever the way you wear it you will love it! With an unrestricted peripheral vision, high side arms graduate to soft, flexible material for additional comfort. Pantoscopic side arms adapt to any facial shape for customised fit and optimal protection with soft grip for a pressure free fit and a version available in Orange 550 lens for specific applications such as surface inspection, mechanical work, ultra-violet light, vulcanization, work with curing light lamp, dentist and medical application.

OPTIONS

1COV23C (1COV23C)
1COV23CKN (1COV23CKN)
1COV23OR550 (1COV23OR550)
1COV23S (1COV23S)
1COV23SKN (1COV23SKN)
1COV23W5 (1COV23W5)

SAFETY STANDARDS

EN 170 • EN 166



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 14 Jul 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



SPECIFICATIONS



RADIATION PROTECTION BREAKDOWN filtering effect
Scale Number
2C



Manufacture's Trademark Swiss One
Swiss One



Low Energy Impact resists a 6 mm, 0.86g ball @ 45 m/s °
Maximum protection for glasses
F

Anti-Scratch/Anti-Fog Coating (23)
Yes

Lightweight
Yes

Soft End Tips - Flex Flat Temple Pressure Free
Yes

Prescription Compatible
Yes



Product Weight
35g



LIGHT TRANSMISSION BREAKDOWN Lens Shade number
1.2



Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use)
1



The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional
T

Lens Base Curve
2.5

Rotating Side Arms
Yes

Metal Free (Di Electric)
Yes

FLEXoFIT Technology
Yes

FEATURES



Anti-mist

Anti-mist



Lens Curve

Lens curve



Lightweight

Lightweight



Soft End Tips

Soft end tips



Metal Free

Metal free



Anti-scratch

Anti-scratch



High Performance Coating

Anti-scratch / anti-fog high performance coating



Rotating Arms

Rotating arms



Soft Nose Pad

Soft nose pad



Flexofit Technology

Flexofit technology

RANGE



DOWNLOADS



[Image Pack \(ZIP\)](#)



[doc-coverlite-updated-15.10.19.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 14 Jul 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

