

ESPECIFICACIONES TÉCNICAS



Swiss One MAXVIEW

3MAX23Y / 3MAX23Y



DESCRIPCIÓN

Lens options to meet your requirements. Thanks to its easy swap lens system, the model MAXVIEW adapts itself to your needs. Available complete in a clear lens version, you then have the option of ordering replacement lenses in clear, yellow, smoke or polarized. RX insert available for prescription lenses.

OPCIONES

3MAX23CREP (1MAX23CREP)
3MAX21POL3.1 (3MAX21POL3.1)
3MAX23Y (3MAX23Y)

NORMAS DE SEGURIDAD

EN 170 • EN 166



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 28 Jun 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.



ESPECIFICACIONES



PROTECCIÓN RADIOLÓGICA Valor de escala de efecto de filtrado
2



Marca del fabricante Swiss One
Swiss One



El impacto de baja energía resiste una bola de 6 mm, 0,86 g a 45 m/s de Máxima protección para gafas
F

Revestimiento antirrayado/antiempañamiento (23)
Sí

Puntas blandas - Templo plano flexible sin presión
Sí



Peso del producto
24g



TRANSMISIÓN DE LA LUZ Valor de oscurecimiento de lente
1,2



Clase óptica (1- Clase 1- alta calidad para uso regular. 2 - Clase 2 - calidad media para uso ocasional. 3 - Clase 3- calidad baja para un uso excepcional).
1



La letra T, inmediatamente después del símbolo de resistencia mecánica, autoriza el uso de partículas de alta velocidad a temperaturas extremas. (-5° y +55°c) opcional
T

Puente nasal blando
Sí

Inserto RX
Maxview insert Compatible

CARACTERÍSTICAS



Anti-mist

Anti-mist



Soft Nose Pad

Soft nose pad



UV 400 Absorption

UV 400 absorption



Anti-scratch

Anti-scratch



Soft End Tips

Soft end tips



RX Insert Compatible

RX Insert compatible

GAMA



DESCARGAR

[Colección de imágenes \(ZIP\)](#)

[doc-maxview.pdf \(PDF\)](#)



JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 28 Jun 2025 / Copyright 2018 - 2025. JSP Limited. All Rights Reserved.

