

TECHNICAL SPECIFICATION



EVO®2 Mid Peak OneTouch™ Slip Ratchet Vented

Black / AJF030-001-100



DESCRIPTION

The EVO®2 Comfort Plus helmet combines a super strong shell for superior all day protection in the widest range of environments, with the comfort benefits of the new Evolution® 3D Adjustment™ harness system. EVO®2 is a true evolution of the long-established MK®2 and MK®3 helmets. The EVO®2 retains the JSP signature styling while incorporating developments first seen in the EVO®8. Packed full of the latest protection technology and features.

OPTIONS

- Black (AJF030-001-100)**
- Blue (AJF030-000-500)
- Green (AJF030-000-300)
- Grey - AJF030-000-400 - Made To Order Min 240 units (AJF030-000-400)
- Orange (AJF030-000-800)
- Pink (AJF030-003-900)
- Red (AJF030-000-600)
- White (AJF030-000-100)
- Yellow (AJF030-000-200)

SAFETY STANDARDS

EN 397



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.



















Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 27 Jul 2024 / Copyright 2018 - 2024, JSP Limited. All Rights Reserved.



SPECIFICATIONS

	Peak Mid		Impact Resistance 50 Joules
	Resistance to Molten Metals and Hot Solids Helmets (optional) Yes		Maximum Temperature +50°C
	Minimum Temperature -30°C		HDPE Shell Yes
	Recyclable Shell		LDPE Harness Yes
	Depth Adjustment 3D Harness		Slip Ratchet Slip
	Universal Accessories Slot Yes		Ventilation Yes
	BSI Kitemark Yes		Reflective Option Optional
	ID card holder Optional		JSPCheck Yes
	Product Weight 402g		Size 53-64cm

FEATURES



Firmest Fit Available

The deep nape strap enables the firmest retention of any helmet, keeping it firmly rooted on the head. The OneTouch™ slip ratchet makes it simple to tighten to the perfect fit.



CR2 Reflective

Using Class RA2, high intensity reflective. CR2 is the biggest step-up in night time visibility/reflectivity of head protection to date. Conforms to Class RA2, EN12899-1.



Supreme Comfort

A traditional 6-point polyethylene harness making the EVO@2 the more economical choice, whilst still providing the same high performance as the EVO@3.



Ventilation Option

Side and rear ventilation for optimum air movement inside the shell, reducing helmet temperatures by an average 2-3 degrees.



3D Adjustment

The polyethylene harness features unique 1-2-3 point depth settings. This offers the most precise fit attainable on an industrial safety helmet.



Accessories

Universal attachment slot enables firm fitting of a range of safety visors and ear defenders.



JSP Logo Express®

Strengthen your corporate identity by applying a company logo on a range of our safety helmets. Minimum order quantities and set-up charges apply.

APPLICATIONS

General guidance only and should not be considered a substitute for a full risk assessment

Agricultural

Airports



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jsp-safety.com / Web: www.jsp-safety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jsp-safety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 27 Jul 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.



Construction and Infrastructure

Oil, Gas and Chemical Companies

Sole Trader

Maritime

Scaffolding and Roofing

Utilities Contractors

LOGO

- Front
- Back
- Sides

VIDEOS

www.youtube.com/watch?v=n9qrN2U0LFk

RANGE



DOWNLOADS

- [Image Pack \(ZIP\)](#)
- [doc-invincible-evo2.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 27 Jul 2024 / Copyright 2018 - 2024. JSP Limited. All Rights Reserved.

