# TECHNICAL SPECIFICATION



# Pioneer™ 2m Single Fall Arrest Lanyard

Pioneer™ 2m Single Fall Arrest Lanyard / FAR0206



## DESCRIPTION

The Pioneer™ fall arrest lanyards are made from the highest quality kernmantle rope and have aluminium connectors, allowing users to feel confident and secure whilst using them, whether moving around or climbing structures.

Complete with 1 aluminium karabiner and 1 aluminium scaffold hook.

## OPTIONS

Pioneer™ 2m Single Fall Arrest Lanyard (FAR0206)

SAFETY STANDARDS

EN 355















#### **SPECIFICATIONS**

Fall Indicator

Yes

Material

Kernmantle Rope Lanyard Diameter 11mm With Black and Red Tracer In the Rope To Indicate The Degradation Of Material.

Sharp Edge

No

Protective Rope Sleeve

Νo

**Delivered With** 

1 Quarter Turn Aluminium Connector. Gate Opening 21mm. Conforms to EN362 Class B. 1 Aluminium Scaffold Hook Gate Opening 60mm. Conforms To EN362 Class A/T Length 2m

Shock Absorber

External

Rope Ends

Stitched And Covered With Polyethylene Protective Sleeve. Abrasion Resistant Thimbles Provided Within Loops.



Product Weight 1000g

#### **APPLICATIONS**

General guidance only and should not be considered a substitute for a full risk assessment

Scaffolding Ventilation

#### DOWNLOADS

Image Pack (ZIP)

doc-far0206-far0210.pdf (PDF)













