# TECHNICAL SPECIFICATION

## EVO® ALTA™ Baseworker™

Blue / ARA170-000-500



### DESCRIPTION

The new EVO® ALTA™ range offers all-round impact protection. The mountaineering-style helmet features a specialised shell structure and internal liner to increase durability and shock absorption performance. Precise adjustment settings enable a secure fit, ensuring the helmet remains stable.
Engineered to maximise compatibility and accessory integration, the EVO® ALTA™ range is an adaptive system with built-in attachment points, and an interchangeable front module, and a selection of 4-point chinstraps for use in a wide range of applications.

EVO® ALTA™ Baseworker™ non vented meets the mandatory shock absorption and penetration resistance requirements of EN 12492 and is fully EN 397 compliant including an EN 397 compliant chinstrap. The 4-point chinstrap is designed to release under force if caught or snagged. EVO®ALTA™ Baseworker™ non vented meets the electrical insulation requirements of EN 397 and EN 50365:2002

### OPTIONS

Black (ARA170-001-100)
**Blue (ARA170-000-500)**
Extra Visibility Orange (ARA170-001-600)
Extra Visibility Yellow (ARA170-00C-700)
Green (ARA170-000-300)
Red (ARA170-000-600)
White (ARA170-000-100)

### SAFETY STANDARDS

EN 397 • EN 50365

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

## SPECIFICATIONS

- Peak: Micro
- Side Impact Resistance: 25 Joules
- Lateral Deformation: Yes
- EN 397 ELECTRICAL INSULATION: 440V
- Minimum Temperature: -40°C
- EPP Liner: Yes
- Textile: Harness
- Depth Adjustment: 3D Harness
- Fitted 4 point chinstrap (EN397 Compliant): Fitted
- Reflective Option: Optional
- JSPCheck: Yes
- Size: 53-64cm
- Impact Resistance: 100 Joules
- Molten Metal: Yes
- EN 50365 ELECTRICAL INSULATION: 1000V
- Maximum Temperature: +50°C
- ABS Shell: Yes
- Recyclable: Shell
- Ventilation: No
- Wheel Ratchet: Yes
- Universal Accessories Slot: Yes
- ID card holder: Optional
- Product Weight: 500g

## FEATURES



### All-Round Protection

EVO® ALTA™ provides all-round impact protection with top, side, front and rear shock absorption performance. The helmet is designed with an extended nape section to offer greater neck coverage.



### Compatibility & Accessories

The EVO® Alta™ range maximises compatibility and accessory integration. Attachment points on the front, sides and rear of the helmet shell enable firm fitting of ear defenders, faceshields, goggle and lamp straps, plus a range of other accessories.



### Maximum Comfort

The Revolution® Flex wheel ratchet harness secures the helmet, eliminating pressure points to provide maximum comfort. Fitted with a replaceable Chamlon™ cotton sweatband and fully compatible with EVO® cooling sweatbands



### Interchangeable Front Module

EVO® ALTA™ features a unique interchangeable front module. Select the integrated ID card holder for on-site identification or choose the logo-ready standard front to apply company branding. Both front modules enable attachment of a helmet lamp and other accessories.



### EPP Liner

EVO® ALTA™ features an internal impact liner to increase shock absorption and penetration protection. Manufactured in expanded polypropylene (EPP), the liner is lightweight and ventilated for comfort.



### Secure Fit

The harness cradles the head to keep the helmet stable with an adjustable 4-point chinstrap for increased security. 3D-Adjustment depth settings enable the most precise fit attainable on a safety helmet.

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

for protection against heat stress.



### 4-Point Chinstrap

The 4-point chinstrap is easy to adjust on the head. Size and anchorage point adjustment enable a tailored fit for different head sizes, ensuring stability and greater comfort.



### Custom Branding

Helmets can be customised to meet a corporate identity. Logo printing is available for the standard front module, helping to increase brand recognition and discourage theft. MOQs apply.

## LOGO

- [x] Front
- [x] Sides

## RANGE

evolta™

## DOWNLOADS

Image Pack (ZIP)



Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.