

TECHNICAL SPECIFICATION



FilterSpec® Pro

FilterSpec® Pro Black/Clear FFP2V / AGE120-201-100



DESCRIPTION

Worn together, safety eyewear and respirators often reduce each other's effectiveness because eyewear frames compromise the seal of the respirator and lead to lens misting and reduced respiratory protection. FilterSpec®Pro combines both protective devices into an integrated unit.

OPTIONS

FilterSpec® Pro Black/Clear FFP2V (AGE120-201-100)
FilterSpec® Pro Black/Clear FFP3V (AGE130-201-100)

SAFETY STANDARDS

EN 170 • EN 149 • EN 166



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.















Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 3 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIONS

 Face Fit Testing Required Yes	 RADIATION PROTECTION BREAKDOWN filtering effect Scale Number 2C
 LIGHT TRANSMISSION BREAKDOWN Lens Shade number 1.2	 Manufacturer's Trademark JSP Dagger
 Optical Class (1 – Class 1 – High quality for regular use. 2 – Class 2 – Medium quality for occasional use. 3 – Class 3 – Low quality for exceptional use) 1	 Medium Energy Impact resists a 6 mm, 0.86g ball @ 120 m/s Maximum protection for goggles. B
 The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures. (-5°C and +55°C) Optional T	 Protection from Liquid Droplets 3
 Protection from Large Dust Particles (up to 40 um grain size) 4	 Resistance to Molten Metals and Hot Solids (optional) 9
Classification FFP2 (Filtering Facepiece Particulate)	 Filter Type P (Protects against solid and liquid aerosols)
Usage NR (Non-reusable)	 Activated Carbon Layer No
Minimum Filtration Efficiency 94% for FFP2 Rated	Maximum Total Inward Leakage (TIL) 8%
Nominal Protection Factor 12	UK Assigned Protection Factor 10
Mask Design Moulded	 Exhalation Valve Yes
Mask Material Polypropylene	Material Polycarbonate lens
Material HDPE mask holder	 Product Weight 144g

FEATURES




Integration

FilterSpec's unique design overcomes the problem of ill fitting masks, fogged lenses and non-conformity that can often occur when one item of PPE compromises another.



Quality Lens

The FilterSpec® Pro goggle features a 5.5 base curve lens. FilterSpec® lenses have a base curve of 6.5. Both offer optimal coverage and feature anti-mist and anti-scratch lens coatings.





Efficient Filter

The easily replaced filters are made from three layers for exceptional performance. Available with low resistance exhalation valve to reduce moisture and CO2 build-up.

RANGE

DOWNLOADS

-  [Image Pack \(ZIP\)](#)
-  [doc-filterspec-pro-ffp2-mask.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 3 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.





JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jpsafety.com / Web: www.jpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 3 of 3 / Issued 3 Apr 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

